Software - DIAG+ CPY - 2730404

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (http://phoenixcontact.com/download)

The Diag+ copy license enables the installation and parallel use of the Diag+ software on multiple workstations. It is a workstation license. A workstation full license is also required.

Product Description

Diag+ is a special diagnostics software tool that has been adapted to PROFINET and INTERBUS and indicates both network errors and the current states of controllers and devices.
Status information, operating functions, plain text messages, and overviews enable fast startup, error localization, and easy orientation in PROFINET and INTERBUS systems.

Your advantages

☑ Integration into other software tools such as visualization systems possible

☑ Management of individual rights of use for various users

☑ Overview for the topology of Ethernet/PROFINET devices in a 2D graphic

☑ Display of error messages with tips for error removal and detailed information on the device type and device state

☑ Display of color symbols for errors and device states

☑ Acknowledgment of INTERBUS error messages

Key Commercial Data

Packing unit	1 pc
GTIN	4 017918 613808
GTIN	4017918613808

Technical data

License information

Intended use for the software	Diagnostics

Functions

Basic functions	Reading in the installed bus structure
	Display of stored messages from the message archive of the controller
	Specification of the accessibility of Ethernet/PROFINET devices
	Start and stop of INTERBUS data traffic

Software - DIAG+ CPY - 2730404

Technical data

Functions

	Diagnostics of INTERBUS FO paths (transmission quality)
	Numerous other diagnostic functions
Integrated function	Diagnostics
	Evaluation
	Startup
	Communication
	Maintenance
	Data acquisition
	Functional safety
Associated hardware	4th generation INTERBUS controller boards, PROFINET controller (Phoenix Contact only)
Number of I/O nodes	not relevant
Configuration	INTERBUS
	PROFINET
Diagnostics	INTERBUS
	PROFINET

Hardware requirements

Hard disk	min. 2 GByte
RAM	min. 2 GByte
CPU	min. 2 GHz, x86 architecture
Interfaces	Serial interface, Ethernet, PCI
Monitor resolution	SXGA (1280 x 1024)
Operating equipment	Keyboard, mouse

Software requirements

Operating system	Windows® 7 Professional SP1 (32-Bit/64-Bit)
	Windows® 7 Ultimate SP1 (32-Bit/64-Bit)
	Windows® 8.1 Professional (32-Bit/64-Bit)
	Windows® 8.1 Enterprise (32-Bit/64-Bit)
	Windows® 10 (32-bit/64-bit), as of Build 1511
Languages supported	German, English, French, Italian, Spanish, Chinese
Supported browsers	Internet Explorer Version 8 or later

Classifications

eCl@ss

eCl@ss 10.0.1	27242501
eCl@ss 4.0	27250200
eCl@ss 4.1	27250200
eCl@ss 5.0	27242500

Software - DIAG+ CPY - 2730404

Classifications

eCl@ss

eCl@ss 5.1	27242500
eCl@ss 6.0	27242500
eCl@ss 7.0	27242501
eCl@ss 8.0	27242501
eCl@ss 9.0	27242501

ETIM

ETIM 2.0	EC001435
ETIM 3.0	EC001435
ETIM 4.0	EC000809
ETIM 5.0	EC000809
ETIM 6.0	EC000809
ETIM 7.0	EC000809

UNSPSC

UNSPSC 6.01	43172015
UNSPSC 7.0901	43201404
UNSPSC 11	43172015
UNSPSC 12.01	43232401
UNSPSC 13.2	43233603
UNSPSC 18.0	43233603
UNSPSC 19.0	43233603
UNSPSC 20.0	43233603
UNSPSC 21.0	43233603

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact](#):
  [2730404](#)