

Fuse modular terminal block - USEN 14 N - 3048357

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Fuse terminal blocks for NEOZED fuse inserts

Your advantages

- ✓ The NEOZED® system features an impressive high current carrying capacity
- ✓ These fuse terminal blocks are designed for NEOZED® fuses

RoHS

Key Commercial Data

Packing unit	10 pc
GTIN	 4 017918 976262
GTIN	4017918976262

Technical data

General

Number of levels	1
Number of connections	2
Nominal cross section	35 mm²
Color	light gray
Insulating material	Duroplast
Flammability rating according to UL 94	V0
Maximum power dissipation for nominal condition	4.06 W
Fuse	D 01 / E 14
Fuse type	Screw cartridge
Rated surge voltage	6 kV
Degree of pollution	2
Overvoltage category	III
Insulating material group	IIIa
Maximum load current	16 A (with 35 mm² conductor cross section)

Fuse modular terminal block - USEN 14 N - 3048357

Technical data

General

Nominal current I_N	16 A (the current is determined by the fuse used)
Nominal voltage U_N	400 V (the voltage is determined by the fuse used)
Open side panel	No
Shock protection test specification	DIN EN 50274 (VDE 0660-514):2002-11
Back of the hand protection	guaranteed
Finger protection	guaranteed
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	165 °C

Dimensions

Width	27 mm
Length	82.7 mm
Pitch	27 mm
Height NS 35/7,5	71.9 mm
Height NS 35/15	79.4 mm

Ambient conditions

Ambient temperature (operation)	-60 °C ... 85 °C
Ambient temperature (storage/transport)	-25 °C ... 55 °C (For a short time, not exceeding 24 h, -60 to +70 °C)
Permissible humidity (storage/transport)	30 % ... 70 %
Ambient temperature (assembly)	-5 °C ... 70 °C
Ambient temperature (actuation)	-5 °C ... 70 °C

Connection data

Conductor cross section solid min.	1.5 mm ²
Conductor cross section solid max.	35 mm ²
Conductor cross section flexible min.	1.5 mm ²
Conductor cross section flexible max.	35 mm ²
Conductor cross section AWG min.	16
Conductor cross section AWG max.	2
Conductor cross section flexible, with ferrule without plastic sleeve min.	1.5 mm ²
Conductor cross section flexible, with ferrule without plastic sleeve max.	25 mm ²
Conductor cross section flexible, with ferrule with plastic sleeve min.	1.5 mm ²
Conductor cross section flexible, with ferrule with plastic sleeve max.	25 mm ²
Cross section with insertion bridge, solid max.	25 mm ²
Cross section with insertion bridge, stranded max.	25 mm ²
2 conductors with same cross section, solid min.	1.5 mm ²
2 conductors with same cross section, solid max.	10 mm ²
2 conductors with same cross section, stranded min.	1.5 mm ²
2 conductors with same cross section, stranded max.	10 mm ²
Two conductors with the same cross section stranded, with ferrule and without plastic sleeve, minimum	1.5 mm ²

Fuse modular terminal block - USEN 14 N - 3048357

Technical data

Connection data

Two conductors with the same cross section stranded, with ferrule and without plastic sleeve, maximum	10 mm ²
Two conductors with the same cross section, flexible, with TWIN ferrules, with plastic sleeve, minimum	1.5 mm ²
Two conductors with the same cross section, flexible, with TWIN ferrules, with plastic sleeve, maximum	10 mm ²
Cross section with insertion bridge, solid max.	25 mm ²
Cross section with insertion bridge, stranded max.	25 mm ²
Connection method	Screw connection
Stripping length	19 mm
Internal cylindrical gage	B8
Screw thread	M6
Tightening torque, min	3.5 Nm
Tightening torque max	4 Nm

Standards and Regulations


Flammability rating according to UL 94	V0
--	----

Environmental Product Compliance

China RoHS	Environmentally Friendly Use Period = 50 years
	For details about hazardous substances go to tab "Downloads", Category "Manufacturer's declaration"

Drawings

Circuit diagram



Classifications

eCl@ss

eCl@ss 10.0.1	27141116
eCl@ss 4.0	27141100
eCl@ss 4.1	27141100
eCl@ss 5.0	27141100
eCl@ss 5.1	27141100

Fuse modular terminal block - USEN 14 N - 3048357

Classifications

eCl@ss

eCl@ss 6.0	27141100
eCl@ss 7.0	27141116
eCl@ss 8.0	27141116
eCl@ss 9.0	27141116

ETIM

ETIM 2.0	EC000899
ETIM 3.0	EC000899
ETIM 4.0	EC000899
ETIM 5.0	EC000899
ETIM 6.0	EC000899
ETIM 7.0	EC000899

UNSPSC

UNSPSC 6.01	30211812
UNSPSC 7.0901	39121411
UNSPSC 11	39121411
UNSPSC 12.01	39121411
UNSPSC 13.2	39121410
UNSPSC 18.0	39121410
UNSPSC 19.0	39121410
UNSPSC 20.0	39121410
UNSPSC 21.0	39121410

Approvals

Approvals

Approvals

EAC / RS / EAC

Ex Approvals

Approval details

EAC	EAC	EAC-Zulassung
-----	------------	---------------

Fuse modular terminal block - USEN 14 N - 3048357

Approvals

RS		http://www.rs-head.spb.ru/en/index.php	17.00013.272
----	---	---	--------------

EAC			RU C- DE.BL08.B.00534
-----	---	--	--------------------------

Accessories

Accessories

DIN rail

DIN rail perforated - NS 35/ 7,5 PERF 2000MM - 0801733



DIN rail perforated, Standard profile, width: 35 mm, height: 7.5 mm, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, length: 2000 mm, color: silver

DIN rail, unperforated - NS 35/ 7,5 UNPERF 2000MM - 0801681



DIN rail, unperforated, Standard profile, width: 35 mm, height: 7.5 mm, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, length: 2000 mm, color: silver

DIN rail perforated - NS 35/ 7,5 WH PERF 2000MM - 1204119



DIN rail perforated, Standard profile, width: 35 mm, height: 7.5 mm, acc. to EN 60715, material: Steel, Galvanized, white passivated, length: 2000 mm, color: silver

DIN rail, unperforated - NS 35/ 7,5 WH UNPERF 2000MM - 1204122



DIN rail, unperforated, Standard profile, width: 35 mm, height: 7.5 mm, acc. to EN 60715, material: Steel, Galvanized, white passivated, length: 2000 mm, color: silver

Fuse modular terminal block - USEN 14 N - 3048357

Accessories

DIN rail, unperforated - NS 35/ 7,5 AL UNPERF 2000MM - 0801704



DIN rail, unperforated, Standard profile, width: 35 mm, height: 7.5 mm, acc. to EN 60715, material: Aluminum, uncoated, length: 2000 mm, color: silver

DIN rail perforated - NS 35/ 7,5 ZN PERF 2000MM - 1206421



DIN rail perforated, Standard profile, width: 35 mm, height: 7.5 mm, acc. to EN 60715, material: Steel, galvanized, length: 2000 mm, color: silver

DIN rail, unperforated - NS 35/ 7,5 ZN UNPERF 2000MM - 1206434



DIN rail, unperforated, Standard profile, width: 35 mm, height: 7.5 mm, acc. to EN 60715, material: Steel, galvanized, length: 2000 mm, color: silver

DIN rail, unperforated - NS 35/ 7,5 CU UNPERF 2000MM - 0801762



DIN rail, unperforated, Standard profile, width: 35 mm, height: 7.5 mm, acc. to EN 60715, material: Copper, uncoated, length: 2000 mm, color: copper-colored

End cap - NS 35/ 7,5 CAP - 1206560



DIN rail end piece, for DIN rail NS 35/7.5

End block

Fuse modular terminal block - USEN 14 N - 3048357

Accessories

End clamp - E/UK - 1201442



End clamp, width: 9.5 mm, height: 35.3 mm, material: PA, length: 50.5 mm, Mounting on a DIN rail NS 32 or NS 35, color: gray

End clamp - E/UK 1 - 1201413



End clamps, for supporting the ends of double-level and three-level terminal blocks, width: 10 mm, color: gray

Fuse

Fuse insert - S 2 A/380 V - 0913016



Fuse insert, nominal current: 2 A, length: 36 mm, diameter: 11 mm, color: pink

Fuse insert - S 4 A/380 V - 0913029



Fuse insert, nominal current: 4 A, length: 36 mm, diameter: 11 mm, color: brown

Fuse insert - S 6 A/380 V - 0913032



Fuse insert, nominal current: 6 A, length: 36 mm, diameter: 11 mm, color: green

Fuse modular terminal block - USEN 14 N - 3048357

Accessories

Fuse insert - S 10 A/380 V - 0913045



Fuse insert, nominal current: 10 A, length: 36 mm, diameter: 11 mm, color: red

Fuse insert - S 16 A/380 V - 0913058



Fuse insert, nominal current: 16 A, length: 36 mm, diameter: 11 mm, color: gray

Insertion bridge

Insertion bridge - EB 36-27 - 3009341



Insertion bridge, pitch: 27 mm, number of positions: 36, color: gray

Insertion bridge - EB 36-27/L1-L2-L3 - 3009354



Insertion bridge, pitch: 27 mm, number of positions: 36, color: gray

Marker carriers

Marker carriers - MA 20X 8 BK - 0814270



Marker carrier, for SS-ZB contactor marking Zack marker strip

Mounting material

Fuse modular terminal block - USEN 14 N - 3048357

Accessories

Adapter sleeve - H 2 A - 0913113



Adapter sleeve, nominal current: 2 A, color: pink

Adapter sleeve - H 4 A - 0913126



Adapter sleeve, nominal current: 4 A, color: brown

Adapter sleeve - H 6 A - 0913139



Adapter sleeve, nominal current: 6 A, color: green

Adapter sleeve - H 10 A - 0913142



Adapter sleeve, nominal current: 10 A, color: red

Screwdriver tools

Screwdriver - SZF 3-1,0X5,5 - 1206612



Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: 1.0 x 5.5 x 150 mm, 2-component grip, with non-slip grip

Phoenix Contact 2020 © - all rights reserved
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG
Flachsmarktstr. 8
32825 Blomberg
Germany
Tel. +49 5235 300
Fax +49 5235 3 41200
<http://www.phoenixcontact.com>

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Phoenix Contact:

3048357