

## Feed-through terminal block - BTP 1,25 GY - 3281106

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Feed-through terminal block, nom. voltage: 690 V, nominal current: 17.5 A, connection method: Push-in connection, number of connections: 4, cross section: 0.14 mm<sup>2</sup> - 1.5 mm<sup>2</sup>, AWG: 26 - 16, width: 7 mm, color: gray, mounting type: NS 35/7,5, NS 35/15

### Your advantages

- ✓ Safety for users thanks to integrated shock protection
- ✓ Reduction in logistics costs with the uniform CLIPLINE complete system accessories
- ✓ Maximum overview thanks to extensive marking and labeling of every terminal point
- ✓ Easy potential distribution with time-saving jumper system
- ✓ Easy and tool-free direct plug-in thanks to push-in multi-conductor connection

RoHS

### Key Commercial Data

|                        |                                                                                                         |
|------------------------|---------------------------------------------------------------------------------------------------------|
| Packing unit           | 50 pc                                                                                                   |
| Minimum order quantity | 50 pc                                                                                                   |
| GTIN                   | <br>4 055626 268941 |
| GTIN                   | 4055626268941                                                                                           |

### Technical data

#### General

|                                        |                     |
|----------------------------------------|---------------------|
| Number of levels                       | 1                   |
| Number of connections                  | 4                   |
| Potentials                             | 1                   |
| Nominal cross section                  | 1.5 mm <sup>2</sup> |
| Color                                  | gray                |
| Insulating material                    | PC                  |
| Flammability rating according to UL 94 | V0                  |
| Rated surge voltage                    | 8 kV                |
| Degree of pollution                    | 3                   |
| Overvoltage category                   | III                 |

# Feed-through terminal block - BTP 1,25 GY - 3281106

## Technical data

### General

|                                                                                           |                                                                                                          |
|-------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------|
| Insulating material group                                                                 | IIIa                                                                                                     |
| Maximum power dissipation for nominal condition                                           | 0.56 W                                                                                                   |
| Maximum load current                                                                      | 17.5 A (The maximum load current must not be exceeded by the total current of all connected conductors.) |
| Nominal current $I_N$                                                                     | 17.5 A                                                                                                   |
| Nominal voltage $U_N$                                                                     | 690 V                                                                                                    |
| Open side panel                                                                           | Yes                                                                                                      |
| Ambient temperature (operation)                                                           | -60 °C ... 85 °C                                                                                         |
| Ambient temperature (storage/transport)                                                   | -25 °C ... 55 °C (For a short time, not exceeding 24 h, -60 to +70 °C)                                   |
| Permissible humidity (storage/transport)                                                  | 30 % ... 70 %                                                                                            |
| Ambient temperature (assembly)                                                            | -5 °C ... 70 °C                                                                                          |
| Ambient temperature (actuation)                                                           | -5 °C ... 70 °C                                                                                          |
| Shock protection test specification                                                       | DIN EN 50274 (VDE 0660-514):2002-11                                                                      |
| Back of the hand protection                                                               | guaranteed                                                                                               |
| Finger protection                                                                         | guaranteed                                                                                               |
| Result of surge voltage test                                                              | Test passed                                                                                              |
| Result of power-frequency withstand voltage test                                          | Test passed                                                                                              |
| Power frequency withstand voltage setpoint                                                | 1.89 kV                                                                                                  |
| Result of the test for mechanical stability of terminal points (5 x conductor connection) | Test passed                                                                                              |
| Result of bending test                                                                    | Test passed                                                                                              |
| Bending test rotation speed                                                               | 10 rpm                                                                                                   |
| Bending test turns                                                                        | 135                                                                                                      |
| Bending test conductor cross section/weight                                               | 0.14 mm <sup>2</sup> / 0.2 kg                                                                            |
|                                                                                           | 1.5 mm <sup>2</sup> / 0.4 kg                                                                             |
| Tensile test result                                                                       | Test passed                                                                                              |
| Result of tight fit on support                                                            | Test passed                                                                                              |
| Tight fit on carrier                                                                      | NS 35                                                                                                    |
| Setpoint                                                                                  | 1 N                                                                                                      |
| Result of voltage-drop test                                                               | Test passed                                                                                              |
| Result of temperature-rise test                                                           | Test passed                                                                                              |
| Requirement temperature-rise test                                                         | Increase in temperature ≤ 45 K                                                                           |
| Short circuit stability result                                                            | Test passed                                                                                              |
| Conductor cross section short circuit testing                                             | 1.5 mm <sup>2</sup>                                                                                      |
| Short-time current                                                                        | 0.18 kA                                                                                                  |
| Result of thermal test                                                                    | Test passed                                                                                              |
| Ageing test for screwless modular terminal block temperature cycles                       | 192                                                                                                      |
| Proof of thermal characteristics (needle flame) effective duration                        | 30 s                                                                                                     |
| Result of aging test                                                                      | Test passed                                                                                              |
| Oscillation, broadband noise test result                                                  | Test passed                                                                                              |
| Test specification, oscillation, broadband noise                                          | DIN EN 50155 (VDE 0115-200):2008-03                                                                      |

# Feed-through terminal block - BTP 1,25 GY - 3281106

## Technical data

### General

|                                                                  |                                                |
|------------------------------------------------------------------|------------------------------------------------|
| Test spectrum                                                    | Service life test category 2, bogie-mounted    |
| Test frequency                                                   | $f_1 = 5 \text{ Hz}$ to $f_2 = 250 \text{ Hz}$ |
| ASD level                                                        | $6.12 \text{ (m/s}^2\text{)}^2/\text{Hz}$      |
| Acceleration                                                     | 3.12 g                                         |
| Test duration per axis                                           | 5 h                                            |
| Test directions                                                  | X-, Y- and Z-axis                              |
| Shock test result                                                | Test passed                                    |
| Test specification, shock test                                   | DIN EN 50155 (VDE 0115-200):2008-03            |
| Shock form                                                       | Half-sine                                      |
| Acceleration                                                     | 30g                                            |
| Shock duration                                                   | 18 ms                                          |
| Number of shocks per direction                                   | 3                                              |
| Test directions                                                  | X-, Y- and Z-axis (pos. and neg.)              |
| Relative insulation material temperature index (Elec., UL 746 B) | 130 °C                                         |

### Dimensions

|                  |         |
|------------------|---------|
| Width            | 7 mm    |
| Length           | 42 mm   |
| Height NS 35/7,5 | 33.5 mm |
| Height NS 35/15  | 41 mm   |

### Connection data

|                                                                            |                                                |
|----------------------------------------------------------------------------|------------------------------------------------|
| Connection method                                                          | Push-in connection                             |
| Stripping length                                                           | 8 mm ... 9 mm                                  |
| Connection in acc. with standard                                           | IEC 60947-7-1                                  |
| Conductor cross section solid min.                                         | 0.14 mm <sup>2</sup>                           |
| Conductor cross section solid max.                                         | 1.5 mm <sup>2</sup>                            |
| Conductor cross section AWG min.                                           | 26                                             |
| Conductor cross section AWG max.                                           | 16                                             |
| Conductor cross section flexible min.                                      | 0.14 mm <sup>2</sup>                           |
| Conductor cross section flexible max.                                      | 1.5 mm <sup>2</sup>                            |
| Min. AWG conductor cross section, flexible                                 | 26                                             |
| Max. AWG conductor cross section, flexible                                 | 16                                             |
| Conductor cross section flexible, with ferrule without plastic sleeve min. | 0.14 mm <sup>2</sup>                           |
| Conductor cross section flexible, with ferrule without plastic sleeve max. | 1.5 mm <sup>2</sup>                            |
| Conductor cross section flexible, with ferrule with plastic sleeve min.    | 0.14 mm <sup>2</sup>                           |
| Conductor cross section flexible, with ferrule with plastic sleeve max.    | 0.75 mm <sup>2</sup>                           |
| Connection cross sections directly pluggable                               | 0.25 mm <sup>2</sup> 1.5 mm <sup>2</sup> 22 16 |
| Conductor cross section solid min.                                         | 0.25 mm <sup>2</sup>                           |
| Conductor cross section solid max.                                         | 1.5 mm <sup>2</sup>                            |
| Conductor cross section flexible, with ferrule without plastic sleeve min. | 0.25 mm <sup>2</sup>                           |

## Feed-through terminal block - BTP 1,25 GY - 3281106

### Technical data

#### Connection data

|                                                                            |                      |
|----------------------------------------------------------------------------|----------------------|
| Conductor cross section flexible, with ferrule without plastic sleeve max. | 1.5 mm <sup>2</sup>  |
| Conductor cross section flexible, with ferrule with plastic sleeve min.    | 0.25 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule with plastic sleeve max.    | 0.75 mm <sup>2</sup> |
| Connection in acc. with standard                                           | JIS 8207-7-1         |
| Conductor cross section solid min.                                         | 0.5 mm <sup>2</sup>  |
| Conductor cross section solid max.                                         | 1.2 mm <sup>2</sup>  |
| Conductor cross section flexible min.                                      | 0.5 mm <sup>2</sup>  |
| Conductor cross section flexible max.                                      | 1.25 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule without plastic sleeve min. | 0.5 mm <sup>2</sup>  |
| Conductor cross section flexible, with ferrule without plastic sleeve max. | 1.25 mm <sup>2</sup> |
| Conductor cross section flexible, with ferrule with plastic sleeve min.    | 0.5 mm <sup>2</sup>  |
| Conductor cross section flexible, with ferrule with plastic sleeve max.    | 0.75 mm <sup>2</sup> |

#### Standards and Regulations

|                                        |               |
|----------------------------------------|---------------|
| Connection in acc. with standard       | IEC 60947-7-1 |
|                                        | JIS 8207-7-1  |
| Flammability rating according to UL 94 | V0            |

#### Environmental Product Compliance

|            |                                                         |
|------------|---------------------------------------------------------|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

### Drawings

Circuit diagram



### Classifications

#### eCl@ss

|               |          |
|---------------|----------|
| eCl@ss 10.0.1 | 27141120 |
| eCl@ss 4.0    | 27141100 |
| eCl@ss 4.1    | 27141100 |
| eCl@ss 5.0    | 27141100 |
| eCl@ss 5.1    | 27141100 |
| eCl@ss 6.0    | 27141100 |
| eCl@ss 7.0    | 27141120 |
| eCl@ss 8.0    | 27141120 |
| eCl@ss 9.0    | 27141120 |

## Feed-through terminal block - BTP 1,25 GY - 3281106

### Classifications

#### ETIM

|          |          |
|----------|----------|
| ETIM 2.0 | EC000897 |
| ETIM 3.0 | EC000897 |
| ETIM 4.0 | EC000897 |
| ETIM 5.0 | EC000897 |
| ETIM 6.0 | EC000897 |
| ETIM 7.0 | EC000897 |

#### UNSPSC

|               |          |
|---------------|----------|
| UNSPSC 6.01   | 30211811 |
| UNSPSC 7.0901 | 39121410 |
| UNSPSC 11     | 39121410 |
| UNSPSC 12.01  | 39121410 |
| UNSPSC 13.2   | 39121410 |
| UNSPSC 18.0   | 39121410 |
| UNSPSC 19.0   | 39121410 |
| UNSPSC 20.0   | 39121410 |
| UNSPSC 21.0   | 39121410 |

### Approvals

#### Approvals

#### Approvals

DNV GL / CSA / UL Recognized / cUL Recognized / EAC / cULus Recognized

#### Ex Approvals

#### Approval details

|        |                                                                                     |                                                                                   |            |
|--------|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|------------|
| DNV GL |  | <a href="https://approvalfinder.dnvgl.com/">https://approvalfinder.dnvgl.com/</a> | TAE00001S2 |
|--------|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------|------------|

|                            |                                                                                     |                                                                                                                                         |       |
|----------------------------|-------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------|-------|
| CSA                        |  | <a href="http://www.csagroup.org/services-industries/product-listing/">http://www.csagroup.org/services-industries/product-listing/</a> | 13631 |
|                            | B                                                                                   | C                                                                                                                                       |       |
| Nominal voltage UN         | 300 V                                                                               | 300 V                                                                                                                                   |       |
| Nominal current IN         | 10 A                                                                                | 10 A                                                                                                                                    |       |
| mm <sup>2</sup> /AWG/kcmil | 26-16                                                                               | 26-16                                                                                                                                   |       |

## Feed-through terminal block - BTP 1,25 GY - 3281106

### Approvals

|                    |                                                                                   |                                                                                                                                                       |              |
|--------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|
| UL Recognized      |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 60425 |
|                    | B                                                                                 | C                                                                                                                                                     |              |
| Nominal voltage UN | 300 V                                                                             | 300 V                                                                                                                                                 |              |
| Nominal current IN | 10 A                                                                              | 10 A                                                                                                                                                  |              |
| mm²/AWG/kcmil      | 26-16                                                                             | 26-16                                                                                                                                                 |              |

|                    |                                                                                   |                                                                                                                                                       |              |
|--------------------|-----------------------------------------------------------------------------------|-------------------------------------------------------------------------------------------------------------------------------------------------------|--------------|
| cUL Recognized     |  | <a href="http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm">http://database.ul.com/cgi-bin/XYV/template/LISEXT/1FRAME/index.htm</a> | FILE E 60425 |
|                    | B                                                                                 | C                                                                                                                                                     |              |
| Nominal voltage UN | 300 V                                                                             | 300 V                                                                                                                                                 |              |
| Nominal current IN | 10 A                                                                              | 10 A                                                                                                                                                  |              |
| mm²/AWG/kcmil      | 26-16                                                                             | 26-16                                                                                                                                                 |              |

|     |                                                                                     |                          |
|-----|-------------------------------------------------------------------------------------|--------------------------|
| EAC |  | RU C-<br>DE.BL08.B.00541 |
|-----|-------------------------------------------------------------------------------------|--------------------------|

|                  |                                                                                     |
|------------------|-------------------------------------------------------------------------------------|
| cULus Recognized |  |
|------------------|-------------------------------------------------------------------------------------|

### Accessories

#### Accessories

##### DIN rail

DIN rail perforated - NS 35/ 7,5 PERF 2000MM - 0801733



DIN rail perforated, Standard profile, width: 35 mm, height: 7.5 mm, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, length: 2000 mm, color: silver

DIN rail, unperforated - NS 35/ 7,5 UNPERF 2000MM - 0801681



DIN rail, unperforated, Standard profile, width: 35 mm, height: 7.5 mm, acc. to EN 60715, material: Steel, galvanized, passivated with a thick layer, length: 2000 mm, color: silver

## Feed-through terminal block - BTP 1,25 GY - 3281106

### Accessories

---

DIN rail perforated - NS 35/ 7,5 WH PERF 2000MM - 1204119



DIN rail perforated, Standard profile, width: 35 mm, height: 7.5 mm, acc. to EN 60715, material: Steel, Galvanized, white passivated, length: 2000 mm, color: silver

DIN rail, unperforated - NS 35/ 7,5 WH UNPERF 2000MM - 1204122



DIN rail, unperforated, Standard profile, width: 35 mm, height: 7.5 mm, acc. to EN 60715, material: Steel, Galvanized, white passivated, length: 2000 mm, color: silver

DIN rail, unperforated - NS 35/ 7,5 AL UNPERF 2000MM - 0801704



DIN rail, unperforated, Standard profile, width: 35 mm, height: 7.5 mm, acc. to EN 60715, material: Aluminum, uncoated, length: 2000 mm, color: silver

DIN rail perforated - NS 35/ 7,5 ZN PERF 2000MM - 1206421



DIN rail perforated, Standard profile, width: 35 mm, height: 7.5 mm, acc. to EN 60715, material: Steel, galvanized, length: 2000 mm, color: silver

DIN rail, unperforated - NS 35/ 7,5 ZN UNPERF 2000MM - 1206434



DIN rail, unperforated, Standard profile, width: 35 mm, height: 7.5 mm, acc. to EN 60715, material: Steel, galvanized, length: 2000 mm, color: silver

## Feed-through terminal block - BTP 1,25 GY - 3281106

### Accessories

DIN rail, unperforated - NS 35/ 7,5 CU UNPERF 2000MM - 0801762



DIN rail, unperforated, Standard profile, width: 35 mm, height: 7.5 mm, acc. to EN 60715, material: Copper, uncoated, length: 2000 mm, color: copper-colored

End cap - NS 35/ 7,5 CAP - 1206560



DIN rail end piece, for DIN rail NS 35/7.5

DIN rail perforated - NS 35/15 PERF 2000MM - 1201730



DIN rail perforated, Standard profile, width: 35 mm, height: 15 mm, similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, length: 2000 mm, color: silver

DIN rail, unperforated - NS 35/15 UNPERF 2000MM - 1201714



DIN rail, unperforated, Standard profile, width: 35 mm, height: 15 mm, similar to EN 60715, material: Steel, galvanized, passivated with a thick layer, length: 2000 mm, color: silver

DIN rail perforated - NS 35/15 WH PERF 2000MM - 0806602



DIN rail perforated, Standard profile, width: 35 mm, height: 15 mm, similar to EN 60715, material: Steel, Galvanized, white passivated, length: 2000 mm, color: silver

## Feed-through terminal block - BTP 1,25 GY - 3281106

### Accessories

DIN rail, unperforated - NS 35/15 WH UNPERF 2000MM - 1204135



DIN rail, unperforated, Standard profile, width: 35 mm, height: 15 mm, similar to EN 60715, material: Steel, Galvanized, white passivated, length: 2000 mm, color: silver

---

DIN rail, unperforated - NS 35/15 AL UNPERF 2000MM - 1201756



DIN rail, unperforated, Standard profile, width: 35 mm, height: 15 mm, similar to EN 60715, material: Aluminum, uncoated, length: 2000 mm, color: silver

---

DIN rail perforated - NS 35/15 ZN PERF 2000MM - 1206599



DIN rail perforated, Standard profile, width: 35 mm, height: 15 mm, similar to EN 60715, material: Steel, galvanized, length: 2000 mm, color: silver

---

DIN rail, unperforated - NS 35/15 ZN UNPERF 2000MM - 1206586



DIN rail, unperforated, Standard profile, width: 35 mm, height: 15 mm, similar to EN 60715, material: Steel, galvanized, length: 2000 mm, color: silver

---

DIN rail, unperforated - NS 35/15 CU UNPERF 2000MM - 1201895



DIN rail, unperforated, Standard profile, width: 35 mm, height: 15 mm, similar to EN 60715, material: Copper, uncoated, length: 2000 mm, color: copper-colored

## Feed-through terminal block - BTP 1,25 GY - 3281106

### Accessories

End cap - NS 35/15 CAP - 1206573



DIN rail end piece, for DIN rail NS 35/15

---

### End block

End clamp - E/NS 35 N BK - 0804271



End clamp, width: 9.5 mm, height: 32.8 mm, material: PA, length: 48.6 mm, color: black

---

### End cover

End cover - D-BT 1,25 GY - 3281129



End cover, length: 42 mm, width: 3.5 mm, height: 26 mm, color: gray

---

End cover - D-BT 1,25 - 3281120



End cover, length: 42 mm, width: 3.5 mm, height: 26 mm, color: black

---

### Insulating sleeve

Insulating sleeve - MPS-IH WH - 0201663



Insulating sleeve, color: white

## Feed-through terminal block - BTP 1,25 GY - 3281106

### Accessories

Insulating sleeve - MPS-IH RD - 0201676

Insulating sleeve, color: red



---

Insulating sleeve - MPS-IH BU - 0201689

Insulating sleeve, color: blue



---

Insulating sleeve - MPS-IH YE - 0201692

Insulating sleeve, color: yellow



---

Insulating sleeve - MPS-IH GN - 0201702

Insulating sleeve, color: green



---

Insulating sleeve - MPS-IH GY - 0201728

Insulating sleeve, color: gray



## Feed-through terminal block - BTP 1,25 GY - 3281106

### Accessories

Insulating sleeve - MPS-IH BK - 0201731

Insulating sleeve, color: black



---

### Jumper

Plug-in bridge - FBS 2-3,5 - 3213014



Plug-in bridge, pitch: 3.5 mm, number of positions: 2, color: red

---

Plug-in bridge - FBS 2-3,5 BU - 3213086



Plug-in bridge, pitch: 3.5 mm, number of positions: 2, color: blue

---

Plug-in bridge - FBS 2-3,5 GY - 3213153



Plug-in bridge, pitch: 3.5 mm, number of positions: 2, color: gray

---

### Labeled terminal marker

Marker for terminal blocks - TMT 6 R CUS - 0824488



Marker for terminal blocks, can be ordered: by line, white, labeled according to customer specifications, mounting type: snap into universal marker groove, snap into flat marker groove, for terminal block width: 6.2 mm, lettering field size: 6.35 x 6.15 mm

---

### Partition plate

## Feed-through terminal block - BTP 1,25 GY - 3281106

### Accessories

Spacer plate - DP PS-3,5 - 3031011



Spacer plate, length: 15.9 mm, width: 3.5 mm, height: 33.5 mm, number of positions: 1, color: red

---

### Planning and marking software

Software - CLIP-PROJECT ADVANCED - 5146040



Multilingual software for convenient configuration of Phoenix Contact products on standard DIN rails.

---

Software - CLIP-PROJECT PROFESSIONAL - 5146053



Multilingual software for terminal strip configuration. A marking module enables the professional marking of markers and labels for identifying terminal blocks, conductors and cables, and devices.

---

### Screwdriver tools

Screwdriver - SZF 0-0,4X2,5 - 1204504



Actuation tool, for ST terminal blocks, also suitable for use as a bladed screwdriver, size: 0.4 x 2.5 x 75 mm, 2-component grip, with non-slip grip

---

Philips screwdriver - SZK PZ0 VDE - 1206447



Screwdriver, PZ crosshead, VDE insulated, size: PZ 0 x 80 mm, 2-component grip, with non-slip grip

## Feed-through terminal block - BTP 1,25 GY - 3281106

### Accessories

Actuation tool - ST-BW - 1207608



Actuation tool, for all 2.5 mm<sup>2</sup> - 4.0 mm<sup>2</sup> spring-cages

---

### Terminal marking

Marker for terminal blocks - TMT 6 R - 0816498



Marker for terminal blocks, Roll, white, unlabeled, can be labeled with: THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, THERMOMARK S1.1, perforated, mounting type: snap into universal marker groove, snap into flat marker groove, for terminal block width: 6.2 mm, lettering field size: 6.35 x 6.15 mm, Number of individual labels: 16000

---

Marker for terminal blocks - TMT (EX9,5)R - 0828295



Marker for terminal blocks, Roll, white, unlabeled, can be labeled with: THERMOMARK ROLL 2.0, THERMOMARK ROLL, THERMOMARK ROLL X1, THERMOMARK ROLLMASTER 300/600, THERMOMARK X1.2, mounting type: snap into universal marker groove, snap into tall marker groove, for terminal block width: 50000 mm, lettering field size: 9.5 x 50000 mm, Number of individual labels: 1

---

Marker for terminal blocks - US-TM 100 - 0829255



Marker for terminal blocks, Card, white, unlabeled, can be labeled with: BLUEMARK ID COLOR, BLUEMARK ID, THERMOMARK PRIME, THERMOMARK CARD 2.0, THERMOMARK CARD, mounting type: snap into universal marker groove, lettering field size: 104 x 9.8 mm, Number of individual labels: 13

---

### Test plug terminal block

Test plugs - PS-3,5 - 3031010



Test plugs, Modular test plug, color: red

## Feed-through terminal block - BTP 1,25 GY - 3281106

### Accessories

Test plugs - PS-3,5/E - 3031012



Test plugs, Individual test plug, color: red

---

Test plugs - MPS-MT - 0201744



Test plugs, with solder connection up to 1 mm<sup>2</sup> conductor cross section, color: gray

---

---

Phoenix Contact 2020 © - all rights reserved  
<http://www.phoenixcontact.com>

PHOENIX CONTACT GmbH & Co. KG  
Flachsmarktstr. 8  
32825 Blomberg  
Germany  
Tel. +49 5235 300  
Fax +49 5235 3 41200  
<http://www.phoenixcontact.com>

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Phoenix Contact:](#)

[3281106](#)