THIS DOCUMENT CONTAINS DATA PROPRIETARY TO PROJECTS UNLIMITED. INC. ANY USE OR			REVISIONS	
THIS DOCUMENT CONTAINS DATA PROPRIETARY TO PROJECTS UNLIMITED, INC. ANY USE OR REPRODUCTION, IN ANY FORM, MITHOUT PRIOR MITTER PERMISSION OF PROJECTS UNLIMITED, INC. 5 PROHIBITED.			LTR DESCRIPTION DATE APP	PROVED
2005, Projects Unlimited Inc. SPECIFICATIONS			- RELEASED FROM ENGINEERING 5/3/06	
PARAMETERS	VALUES	UNITS		
RATED INPUT POWER	1	W		
MAX INPUT POWER	2	W		
MPEDANCE	16±15%	ОНМ		
OUTPUT SPL @ 0.1W/0.5M (AT 0.8, 1, 1.2, 1.5 kHz)	78±3	dBA		
DISTORTION (MAX.)	5%	_		
RESONANT FREQUENCY	600±20%	Hz		
FREQUENCY RANGE	600 ~ 5200	Hz		
HOUSING MATERIAL	METAL	_		
CONE MATERIAL	MYLAR	_		
MAGNET MATERIAL	Nd-Fe-B	-		
OPERATING TEMPERATURE	-20 ~ +60	.		
WEIGHT	9	grams		
¢40±0.3 ¢36.2			ø18.3 • 2.4±0.3	
NOTES:			UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN MULLINERSTOLERANCES ARE ±0.5 AND ANGLES ARE ±3.	
1. ALL DIMENSIONS ARE IN MILLIMETERS.			APPROVALS DATE SPEAKER	
2. SPECIFICATION SUBJECT TO CHANGE OR WITHDRAWAL WITHOUT NOTICE.			DRAWN J.D. 5/06	
3. THIS PART IS ROHS 2002/95/EC COMPLIANT			CHECKED E.P. 5/06 SIZE DRAWING NO. APPROVED B.R. 5/06 A ASO4016MR-R	
		AS04016MR-R.DWG	DO NOT SCALE DRAWING SCALE: N.T.S. SHEET 1 OF	1

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

PUI Audio: AS04016MR-R