		REV CHANGE					D	ATE	DRN	СНК	
		Drawn						24/17	SJ	т	
						TOLEI	RANCE DETAILS				
		1			D	+0.010 [+0	0.25] 5	HL	±0.010	[±0.25]	
				2	L	±0.015 [±0		SD	±0.005	.005 [±0.13]	
				3	W	+0.005 [+0	0.13] 7	SL	±0.010	.010 [±0.25]	
				4	HD	+ 0.015 [+ 0	.38]				
STRAIGHT KNURL TPI 35 (0.045(W) [1.14] Ø 5/16 (HD) [7.94] 1/16 (D) [1.59] 3/16 [4.76] (HL) NOTES: 1. Material : Stainless Steel 2. Finish : 3. ASME Y14.5-M - 2009 4. All Drawing Dimensions are in Inches 5. Unless otherwise specified; Edge Breat Partie or Counterview 0.005 0.015	[mm]	5 [14.; (SL) — 27/;	3] 32 [21.43] (L) –				•	82°±	<sup>-</sup> L)		
Radii or Countersinks 0.005-0.015			TOLERANCES			COMPONENT		PAN	EL SCRE		
DAE	This Drawing is the Property o It contains confidential, propri		ALL DIMENSIONS ARE INCHES (UNLESS OTHERWISE SPECIFIED METALLIC	,		010	8-SS				
95 Silvermine Rd.,Seymour CT 06483 Tel: 203-888-2133,Fax: 203-888-9860			LENGTHS =: 6 INCHES ± 0.000<br LENGTH >: 6 INCHES ± 0.010 DIAMETERS: ± 0.005	5						5.12	
			NON-METALLIC LENGTH: ±0.010 DIAMETERS: ± 0. INTERNAL THREADS:	.010	CAP	TIVE PANEL	ANEL SCREW STYLE 1			HEET	
· ··· _ ·· · · · · · · · · · · · · · ·	except as authorized by m	u .	MINIMUM THREAD DEPTH						1	of 1	

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

RAF Electronic Hardware: 0108-SS