		REV CHANGE					DATE			DRN	СНК
	-	Drawn						02/24/17		SJ	т
	L			TOL							
		-	1	D	+0.010 [+ -0.000 [-0	0.25] .001	5	HL	±0.010	[±0.25]	
			-	2	L	±0.015 [±0		6	SD	±0.005	[±0.13]
				3	W	+ 0.005 [+ -0.000 [-0.	.00]	7	SL	±0.010	[±0.25]
				4	HD	+ 0.015 [ + -0.000 [-0	0.38] .00]	8	TL	±0.015	[±0.38]
STRAIGHT KNURL TPI 30 (1/16 (W) [1.59] (7/16 (HD) [11.11] (7/16 (D) [1.59] (1/16 (D) [1.59] (1/4 [6.35] (HL) (1/4 [6.35] (HL) (1/4 [6.35] (HL) (1/5) (	[mm]	[14.: SL)	3] 6 [23.81] (L) —			[	82 <sup>°</sup> 3/8 9.53	°±⁵ ↓ (T)	L)		
Radii or Countersinks 0.005-0.015			TOLERANCES			OMPONEN	I		PANE		CALE
(RAF)	This Drawing is the Property of It contains confidential, proprie	RAF. ALL DIMENSIONS ARE INCHES (UNLESS OTHERWISE SPECIFIE METALLIC		» 0166				6-SS			3.66
	information that is RAF property. Do										HEET
Tel: 203-888-2133,Fax: 203-888-9860 except as authorized by RAF.				INTERNAL THREADS:				CAPTIVE PANEL SCREW STYLE 1			
	MINIMUM THREAD DEPTH										of 1

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

RAF Electronic Hardware: 0166-SS