

SCHOTTKY BARRIER RECTIFIER

VOLTAGE RANGE 20 to 50 Volts CURRENT 50 Ampere

FEATURES


- * Low switching noise
- * Low forward voltage drop
- * Low thermal resistance
- * High current capability
- * High switching capability
- * High surge capability
- * High reliability

MECHANICAL DATA

- * Case: To-247 molded plastic
- * Epoxy: Device has UL flammability classification 94V-O
- * Lead: MIL-STD-202E method 208C guaranteed
- * Mounting position: Any
- * Weight: 6.10 grams



TO-247



Dimensions in inches and (millimeters)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS

Ratings at 25 °C ambient temperature unless otherwise specified.

Single phase, half wave, 60 Hz, resistive or inductive load.

For capacitive load, derate current by 20%.

MAXIMUM RATINGS (@ TA=25 °C unless otherwise noted)

RATINGS	SYMBOL	SR5020C	SR5030C	SR5035C	SR5040C	SR5045C	SR5050C	UNITS
Maximum Recurrent Peak Reverse Voltage	V_{RRM}	20	30	35	40	45	50	Volts
Maximum RMS Voltage	V_{RMS}	14	21	25	28	32	35	Volts
Maximum DC Blocking Voltage	V_{DC}	20	30	35	40	45	50	Volts
Maximum Average Forward Rectified Current at Derating Case Temperature	I_O	50						Amps
Peak Forward Surge Current 8.3 ms single half sine-wave superimposed on rated load (JEDEC method)	I_{FSM}	400						Amps
Typical Thermal Resistance (Note 1)	$R_{\theta JC}$	1.2						°C/W
	$R_{\theta JA}$	24						
Operating Temperature Range	T_J	150						°C
Storage Temperature Range	T_{STG}	-55 to + 150						°C

ELECTRICAL CHARACTERISTICS(@TA=25 °C unless otherwise noted)

CHARACTERISTICS		SYMBOL	SR5020C	SR5030C	SR5035C	SR5040C	SR5045C	SR5050C	UNITS	
Maximum Instantaneous Forward Voltage at 25.0A DC		V _F	.65						.75	Volts
Maximum Average Reverse Current	@T _A = 25°C	I _R	1.0							mA
at Rated DC Blocking Voltage	@T _A = 100°C		10							mA

NOTES : 1. Thermal Resistance : Heat-sink mounted.
2. Suffix "A" = Common Anode.
3."Fully ROHS compliant","100% Sn plating (Pb-free)".

2006-11
REV:B

RATING AND CHARACTERISTICS CURVES (SR5020C THRU SR5050C)




FIG.1 TYPICAL FORWARD CURRENT DERATING CURVE




FIG.2 TYPICAL REVERSE CHARACTERISTICS




FIG.3 TYPICAL INSTANTANEOUS FORWARD CHARACTERISTICS




FIG.4 MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT

DISCLAIMER NOTICE

Rectron Inc reserves the right to make changes without notice to any product specification herein, to make corrections, modifications, enhancements or other changes. Rectron Inc or anyone on its behalf assumes no responsibility or liability for any errors or inaccuracies. Data sheet specifications and its information contained are intended to provide a product description only. "Typical" parameters which may be included on RECTRON data sheets and/ or specifications can and do vary in different applications and actual performance may vary over time. Rectron Inc does not assume any liability arising out of the application or use of any product or circuit.

Rectron products are not designed, intended or authorized for use in medical, life-saving implant or other applications intended for life-sustaining or other related applications where a failure or malfunction of component or circuitry may directly or indirectly cause injury or threaten a life without expressed written approval of Rectron Inc. Customers using or selling Rectron components for use in such applications do so at their own risk and shall agree to fully indemnify Rectron Inc and its subsidiaries harmless against all claims, damages and expenditures.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Rectron:](#)

[SR5040C](#) [SR5045C](#) [SR5020C](#) [SR5050C](#) [SR5035C](#) [SR5030C](#)