the swiss power source



396 MERCURY SR726W (SR59) Watch Battery OEM Swiss Made

Technical Data Sheet


Specifications

Chemical system Nominal Voltage Capacity Operating Temperature* Self Discharge Weight Zinc / Monovalent Silver Oxide, high drain 1,55 V 32 mAh, Discharge over 25,5 kΩ at 20°C to 1,2 V -10°C – 60°C Less than 10% per year at 20°C ~0,48 g

Dimensions

(according IEC 60086-3)

Diameter	7,90 mm (0,311")
Height	2,60 mm (0,102")



Discharge Curve

			1.7 1.6						
		2	1.5					$ \longrightarrow $	
Constant Load	25,5 kΩ	Voltage [V]	1 .4						
Starting Drain Temperature	61,9 μΑ 20°C		1.3						$\left \right $
· · · · · · · · · · · · · · · · · · ·	20 0		1.2						
			1.1	 0 1	00 2	00 30	00 400	0 5(00 600
						Tim	e [h]		

Information and contents in this data sheet are for reference purpose only. They do not constitute any warranty or representation and are subject to change without notice. For most current information and further details, please contact your Renata representative. For safety related information please consult the PSDS document related to that product or product family. *Condensing humidity not allowed

Rev. 396MF_OEM.04 2014/10

Renata SA CH-4452 Itingen/Switzerland Tel. +41 (0)61 975 75 75 Fax. +41 (0)61 975 75 95 sales@renata.com www.renata.com

A COMPANY OF THE SWATCH GROUP

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Renata:

<u>396.TS 0% HG</u> <u>396.MP 0% HG</u>