



Versatile Medical Class II EMC/RFI Filter



- Medical filter suitable for compliance with Protection Class II (ME) according IEC 60601-1
- Fulfills the requirement for two MOPP (means of patient protection), compliant with IEC/EN 60601-1
- No leakage current to earth
- Rated currents up to 15 A
- Excellent performance/size ratio
- Front mount, rear mount and snap-in versions (B, MB and S1B type)
- Plastic enclosure for higher dielectric strength insulation
- Fast-on terminals or wire leads
- V-lock compatible



Performance indicators

Attenuation performance



Technical Specifications

Maximum continuous operating voltage	250 VAC, 50/60 Hz
Nominal operating voltage	230 VAC
Rated currents	1 to 15 A @ 40°C
Operating frequency	DC to 400 Hz
High potential test voltage	P → N 760 VAC for 2 s P/N → Ext. insulation 4 kVAC for 60 s acc. IEC 60601-1
Overvoltage category	II acc. IEC 60664-1
Pollution degree	2 acc. IEC 60664-1
Surge pulse protection (Z type)	Helps compliance to IEC61000-4-5 (Differential Mode only)
Temperature range (operation and storage)	-40°C to +100°C (40/100/21)
Protection category	IP 40 according to IEC 60529 (front side, with inserted plug)
Flammability corresponding to	Laces for -07 version: UL 94 VW-1 Plastic Material: UL 94 V-0 Laces for -07 version: UL 94 VW-1
Vibration and shock	3M4 acc. IEC 60721-3-3
Design corresponding to	up to 15A: UL 60939-3, CSA Std C22.1 No. 8-13 up to 10A: IEC/EN 60939-3, GB/T15287, GB/T15288
MTBF (Mil-HB-217F)	>1,000,000 h @ 40°C/230 V

Approvals & Compliances



The FN9274 IEC inlet filter is suitable for compliance with Class II ME equipment. It incorporates an EMC filter into a C18 IEC inlet that offers excellent filter attenuation in a compact housing.

The filter is available with two connection variants on the load side. The cable version is touch-safe by default. The pins of the fast-on-version are recessed in the plastic housing. In combination with insulated crimp connectors Class II compliance can be achieved for Fast-on version.

The requirements for Two MOPP in IEC 60601-1:2005 + A1 regarding Leakage Currents, Insulation and Air Clearance and Creepage Distances and Ball Pressure test are fulfilled.


Features and Benefits

- Suitable for class II Medical Equipment (ME)
- Fulfills the requirements for Two MOPP in IEC 60601-1 - Medical electrical equipment
- Fulfills the requirements in IEC/EN 62368-1 - Audio/video, information and communication technology equipment
- Fulfills the requirements in IEC/EN 60950-1 - Information technology equipment
- Fulfills the requirements in IEC/EN 60335-1 - Household and similar electrical appliances
- Fulfills the requirements for Reinforced Insulation in IEC 61010-1 - Safety requirements
- All versions certified according UL/IEC 60939-3, C22.2 No. 8, CQC/CCC GB/T15287 and GB/T15288

Typical Applications

- General medical devices (MDD)
- In-vitro diagnostic medical devices (IVDD)
- Test and measurement equipment
- Portable electrical and electronic equipment
- Single-phase power supplies, switch-mode power supplies (SMPS)
- Audio / video / communication equipment (IEC/UL 62368-1)

Typical electrical schematic




Filter Selection Table - Classic

Filter	Buy	Rated current @ 40°C	Leakage current	Inductance L1	Capacitance Cx	Resistor R	Input connections	Output connections	Weight
		[A]	[mA]	[mH]	[µF]	[MΩ]		<div><div></div><div>*</div></div>	[g]
FN9274XXB-1-ZZ		1	0.0	41.1	0.22	1	C18	-05 -07	<40
FN9274XXB-2-ZZ		2	0.0	20.1	0.22	1	C18	-05 -07	<40
FN9274XXB-4-ZZ		4	0.0	7.2	0.22	1	C18	-05 -07	<40
FN9274XXB-6-ZZ		6	0.0	3.2	0.22	1	C18	-05 -07	<40
FN9274XXB-10-ZZ		10	0.0	1.3	0.22	1	C18	-05 -07	<40
FN9274XXB-15-ZZ		15	0.0	0.4	0.22	1	C18	-05 -07	<40

Test conditions: Temperature: 25°C±2°C; measuring frequency for inductance: 1 kHz, 50 mV
Tolerances: Inductance: +50%, -30%; capacitance: ±20%; resistance: ±10%. For mechanical tolerances, please refer to the mechanical data section
* Standard length is 160 mm

Product selector

FN 9274 xx B -yy-zz



For example FN9274MB-15-05:

- FN9274 IEC inlet with
- rear mount flanges (M),
- 15A rated current (15) and
- fast-on terminals (05).


Design-in recommendation:

- EMC and functional test with FN9274B-XX-05 (safety stock all currents - front mount, fast-on types)
- Mechanical integration with FN9274XXB-15-ZZ (safety stock for all variants - 15A-types)


Typical Filter Attenuation

Per CISPR 17 / symmetrical 50 Ω/50 Ω - Differential Mode (DM) / asymmetrical 50 Ω/50 Ω - Common Mode (CM)


1 A




2 A




4 A




6 A



10 A




15 A




Mechanical Data - Rear Mount

FN9274MB-XX-05




FN9274MB-XX-07




For dimensions [mm] without tolerances: ISO 2768-m / EN22768-m applies

Mechanical Data - Snap-in

FN9274S1B-XX-05



FN9274S1B-XX-07



CURRENT [A]	LACE
1	AWG 18
2	AWG 18
4	AWG 18
6	AWG 18
10	AWG 16
15	AWG 16

For dimensions [mm] without tolerances: ISO 2768-m / EN22768-m applies

Headquarters, Global
Innovation and
Development

Switzerland
Schaffner Group
Industrie Nord
Nordstrasse 5
4542
Luterbach
+41 32 681 66 26
info@schaffner.com

To find your local partner within
Schaffner's global network [schaffner.com](https://www.schaffner.com)

© 2025 Schaffner Group

The content of this document has been carefully checked and understood. However, neither Schaffner nor its subsidiaries assume any liability whatsoever for any errors or inaccuracies of this document and the consequences thereof. Published specifications are subject to change without notice. Product suitability for any area of application must ultimately be determined by the customer. In all cases, products must never be operated outside their published specifications. Schaffner does not guarantee the availability of all published products. This disclaimer shall be governed by substantive Swiss law and resulting disputes shall be settled by the courts at the place of business of Schaffner Holding AG. Latest publications and a complete disclaimer can be downloaded from the Schaffner website. All trademarks recognized.

Sales and Application
Centers

Finland
Schaffner Oy
Lohjanharjuntie 1109
08500
Lohja
+ 358 50 468 72 84
finlandsales@schaffner.com

France
Schaffner EMC S.A.S.
16-20 Rue Louis Rameau
95875
Bezons
+33 1 34 34 30 60
francesales@schaffner.com

Germany
Schaffner Deutschland GmbH
Ohiostr. 8
76149
Karlsruhe
+49 721 56910
germanysales@schaffner.com

Italy
Schaffner EMC S.r.l.
Via Ticino, 30
20900
Monza (MB)
+39 335 120 44 32
italysales@schaffner.com

Japan
Schaffner EMC K.K.
ISM Sangenjaya 7F
1-32-12 Kamiuma Setagaya-ku
154-0011
Tokyo
+81 3 5712 3650
japansales@schaffner.com

Singapore
Schaffner EMC Pte Ltd.
Blk 3015A Ubi Road 1 #05-09 Kampong Ubi
Industrial Estate
408705
Singapore
+65 63773283
singaporesales@schaffner.com

Sweden
Schaffner EMC AB
Östermalmströg 1
114 42
Stockholm
+46 8 5050 2425
swedensales@schaffner.com

Switzerland
Schaffner EMV AG
Industrie Nord
Nordstrasse 5
4542
Luterbach
+41 32 681 66 26
switzerlandsales@schaffner.com

India
Schaffner India Pvt. Ltd
Regus World Trade Centre
WTC 22nd Floor Unit No 2238 Brigade
Gateway Campus 26/1 Dr. Rajkumar Road
Malleshwaram (W)
560055
Bangalore
+91 8067935355
indiasales@schaffner.com

United Kingdom
Schaffner Ltd.
Suite 1 Oakmede Place
Terrace Road
RG42 4JF
Binfield
+44 118 9770070
schaffner.uksales@te.com

United States
Schaffner EMC Inc.
52 Mayfield Avenue
Edison, New Jersey
+1 732 225 9533
usasales@schaffner.com

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Schaffner:](#)

[FN9274B-10-05](#) [FN9274B-10-07](#) [FN9274B-1-05](#) [FN9274B-1-07](#) [FN9274B-15-05](#) [FN9274B-15-07](#) [FN9274S1B-2-05](#) [FN9274S1B-2-07](#) [FN9274S1B-4-05](#) [FN9274S1B-4-07](#) [FN9274S1B-6-05](#) [FN9274S1B-6-07](#) [FN9274S1B-10-05](#) [FN9274S1B-10-07](#) [FN9274S1B-1-05](#) [FN9274S1B-1-07](#) [FN9274S1B-15-05](#) [FN9274S1B-15-07](#) [FN9274MB-2-05](#) [FN9274MB-2-07](#) [FN9274MB-4-05](#) [FN9274MB-4-07](#) [FN9274MB-6-05](#) [FN9274MB-6-07](#) [FN9274MB-10-05](#) [FN9274MB-10-07](#) [FN9274MB-1-05](#) [FN9274MB-1-07](#) [FN9274MB-15-05](#) [FN9274MB-15-07](#) [FN9274B-2-05](#) [FN9274B-2-07](#) [FN9274B-4-05](#) [FN9274B-4-07](#) [FN9274B-6-05](#) [FN9274B-6-07](#)