Product data sheet Characteristics

AP7902BGRNX874

Rack PDU, Switched, 2U, 30A, 120V, (16)5-20, Full Paint Aetna Green



Overview

Lead time Special Order - Call for Quoted Lead Times

General

Provided Equipment	Cord retention bracket(s)	
	Horizontal mounting brackets	
	User Manual	
	Installation guide	

Physical

•		
Cable length	10 ft (3.05 m)	
Color	Black	
Depth	4.49 in (11.4 cm)	
Height	3.50 in (8.9 cm)	
Product Weight	9.92 lb(US) (4.5 kg)	
Width	17.52 in (44.5 cm)	

Input

Line Rated Current	24 A	
Permissible voltage	100120 V	
Input current limits	30 A	
Load Capacity	2880 VA	
Input Frequency	50/60 Hz	
Plug standard	NEMA L5-30P	
Nominal Input Voltage	100 V 120 V	

Output

Number of power socket outlets	16 NEMA 5-20R
--------------------------------	---------------

Conformance

Product Certifications	CUL Listed CSA Industry Canada UL Listed	
Standards	FCC Part 15 class A ICES-003	
	UL 60950	

Environmental

Ambient Air Temperature for Operation	32113 °F (045 °C)
Relative Humidity	095 %
Operating altitude	010000 ft
Ambient Air Temperature for Storage	-13149 °F (-2565 °C)
Storage Relative Humidity	095 %
Storage altitude	050000 ft (0.0015240.00 m)

Ordering and shipping details

Package weight(Lbs)	14.44 lb(US) (6.55 kg)

Packing Units

Package 1 Height	5.51 in (14 cm)
Package 1 width	20.00 in (50.8 cm)
Package 1 Length	14.49 in (36.8 cm)

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	[™] REACh Declaration	
EU RoHS Directive	Compliant E EU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	₫Yes	
Environmental Disclosure	Product Environmental Profile	
Circularity Profile	☐ End Of Life Information	
Optimized Energy Efficiency	Energy efficient product	
Take-back	Take-back program available	

Contractual warranty

Warranty 2 years repair or replace	Warranty	2 years repair or replace
------------------------------------	----------	---------------------------

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric:

AP7902BGRNX874