



Overview

| | |
|--------------|---|
| Presentation | The Step-Down Transformer converts high voltage (208 or 200 VAC) output into low voltage (120 or 100 VAC) output for powering low voltage AC equipment. |
| Lead time | Usually in Stock |

General

| | |
|--------------------|---------------------------------------|
| Provided Equipment | User Manual Rack Mounting brackets |
|--------------------|---------------------------------------|

Physical

| | |
|----------------|-------------------------|
| Color | Black |
| Depth | 24.02 in (61 cm) |
| Height | 3.50 in (8.9 cm) |
| Product Weight | 95.20 lb(US) (43.18 kg) |
| Width | 17.52 in (44.5 cm) |

Input

| | |
|-----------------------|-------------|
| Permissible voltage | 208 V |
| Max line current | 24 A |
| Input current limits | 30 A |
| Load Capacity | 5000 VA |
| Plug standard | NEMA L6-30P |
| Nominal Input Voltage | 208 V |

Output

| | |
|--------------------------------|---------------|
| Max current draw | 24 A |
| Number of power socket outlets | 12 |
| Efficiency | 90 % |
| Number of power socket outlets | 12 NEMA 5-20R |
| Output voltage | 120 V |

Conformance

| | |
|------------------------|------------------|
| Product Certifications | CSA |
| Standards | OSHPD UL 1778 |

Environmental

| | |
|---------------------------------------|----------------------------------|
| Ambient Air Temperature for Operation | 32...104 °F (0...40 °C) |
| Relative Humidity | 0...95 % |
| Operating altitude | 0...10000 ft |
| Ambient Air Temperature for Storage | 5...113 °F (-15...45 °C) |
| Storage Relative Humidity | 0...95 % |
| Storage altitude | 0...50000 ft (0.00...15240.00 m) |




Ordering and shipping details

| | |
|---------------------|-----------------------|
| GTIN | 00731304249139 |
| Package weight(Lbs) | 110.23 lb(US) (50 kg) |

Packing Units

| | |
|------------------|--------------------|
| Package 1 Height | 10.00 in (25.4 cm) |
| Package 1 width | 24.49 in (62.2 cm) |
| Package 1 Length | 37.52 in (95.3 cm) |

Offer Sustainability

| | |
|-----------------------------|---|
| Sustainable offer status | Green Premium product |
| REACH Regulation |  REACH Declaration |
| EU RoHS Directive | Compliant  EU RoHS Declaration |
| Lead free | Yes |
| Mercury free | Yes |
| RoHS exemption information |  Yes |
| Optimized Energy Efficiency | Energy efficient product |
| Take-back | Take-back program available |

Contractual warranty

| | |
|----------|---------------------------|
| Warranty | 2 years repair or replace |
|----------|---------------------------|

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Schneider Electric:](#)

[AP9626](#)