GV4AS287

MX - voltage release - 220...240 V AC 50Hz - 208...277 V AC 60Hz - for TeSys GV4





Main

Range	TeSys
Device short name	MX
Product or component type	Voltage release
Device application	Control
Range compatibility	TeSys GV4 TeSys BV4
Voltage release type	Shunt trip release
[Uc] control circuit voltage	277 V AC 60 Hz 220240 V AC 50 Hz 208240 V AC 60 Hz

Complementary

[Ui] rated insulation voltage	277 V conforming to IEC 60947-1	
Threshold tripping voltage	0.71.1 Un failsafe opening < 0.7 Un possible opening	
Impulse duration	>= 20 ms	
Mounting mode	Internal mounting	
Maximum inrush power in VA	6 VA	
Maximum hold-in power consumption in VA	10 VA	
Mechanical durability	20000 Cycles	
Operating time	< 50 ms	
Connections - terminals	Spring terminals 1 0.51.5 mm² - cable stiffness: flexible without cable end	
Wire stripping length	8 Mm	

Environment

Quantity per set	Set of 1

Packing Units

Unit Type of Package 1	PCE	
Number of Units in Package 1	1	
Package 1 Weight	42 G	
Package 1 Height	3.5 Cm	
Package 1 width	8.5 Cm	
Package 1 Length	6.1 Cm	
Unit Type of Package 2	BB1	
Number of Units in Package 2	10	

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not inherence in not to be used for determining suitability or reliability of these products for specific user applications. It is the douty of any sub user or integrator to perform the appropriate and complete risk analysis, evaluating of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

Package 2 Weight	0.5 Kg
Package 2 Height	8.8 Cm
Package 2 width	12.9 Cm
Package 2 Length	18.5 Cm
Unit Type of Package 3	S03
Number of Units in Package 3	60
Package 3 Weight	3.441 Kg
Package 3 Height	30 Cm
Package 3 width	30 Cm
Package 3 Length	40 Cm

Offer Sustainability

Sustainable offer status	Green Premium product	
REACh Regulation	☑ REACh Declaration	
EU RoHS Directive	Compliant EEU RoHS Declaration	
Mercury free	Yes	
RoHS exemption information	€Yes	
China RoHS Regulation	China RoHS Declaration	
Environmental Disclosure	Product Environmental Profile	
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins	
California proposition 65	WARNING: This product can expose you to chemicals including: DIN-P, which is known to the State of California to cause cancer, and DID-P, which is known to the State of California to cause birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov	

Product Life Status: Commercialised

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: GV4AS287