## Product data sheet Characteristics

## HMIGTO2315FW

# Advanced touchscreen panel, Harmony GTO, 5.7 Color Touch QVGA Stainless, logo removed

Product availability: Non-Stock - Not normally stocked in distribution facility

Price\*: 2777.50 USD



#### Main

Range of product	Harmony GTO	
Product or Component Type	Advanced touchscreen panel	
Display colour	65536 colours	
Display size	5.7 inch	
Supply	External source	
Battery type	Lithium internal RAM 100 days 5 day(s) 10 year(s)	
Provided Equipment	1 protective cover	

#### Complementary

Touchscreen display	
Backlit colour TFT LCD	
320 x 240 pixels QVGA	
1024 x 1024	
Resistive film, 1000000 cycles	
50000 hours white 77 °F (25 °C)	
16 levels by touch panel 16 levels by software	
Japanese (ANK, Kanji) ASCII Taiwanese (traditional Chinese) Korean Chinese (simplified Chinese)	
24 V DC	
19.228.8 V	
30 A	
<ul><li>6.5 W when power is not supplied to external devices</li><li>4.5 W when backlight is OFF</li><li>5 W when backlight is dimmed</li><li>10.5 W</li></ul>	
	Backlit colour TFT LCD  320 x 240 pixels QVGA  1024 x 1024  Resistive film, 1000000 cycles  50000 hours white 77 °F (25 °C)  16 levels by touch panel 16 levels by software  Japanese (ANK, Kanji) ASCII Taiwanese (traditional Chinese) Korean Chinese (simplified Chinese)  24 V DC  19.228.8 V  30 A  6.5 W when power is not supplied to external devices 4.5 W when backlight is OFF 5 W when backlight is dimmed

Local signalling	Status I ED green, steady offline	
Local signalling	Status LED green, steady offline Status LED green, steady operating	
	Status LED orange, flashing software starting up	
	Status LED red, steady power supply (ON)	
	Status LED clear, faded power supply (OFF)	
	COM2 LED yellow, steady data is being transmitted COM2 LED yellow, faded no data transmission	
	SD card LED green, steady card is inserted	
	SD card LED green, faded card is not inserted or is not being accessed	
Software designation	Vijeo Designer configuration software >= V6.1	
Memory description	Flash EPROM, 96 MB	
Data backed up	512 kB internal RAM SRAM)	
Data storage equipment	SD card, <= 32 GB SDHC card, <= 32 GB	
Downloadable protocols	Schneider Electric Modicon Modbus	
	Schneider Electric Modicon Uni-TE Schneider Electric Modicon Modbus Plus	
	Schneider Electric Modicon FIPWAY	
	Mitsubishi Melsec third party protocols	
	Omron Sysmac third party protocols	
	Rockwell Automation Allen-Bradley third party protocols	
	Siemens Simatic third party protocols Schneider Electric Modicon Modbus TCP	
Integrated connection type	COM1 serial link SUB-D 9 RS232C 2400115200 bps	
	COM2 serial link RJ45 RS485 2400115200 bps	
	COM2 serial link RJ45 RS485 187.5 kbps Siemens MPI	
	Ethernet RJ45 10BASE-T/100BASE-TX	
	Ethernet RJ45 IEEE 802.3 USB 2.0 type A	
	USB 2.0 type mini B	
Product mounting	Flush mounting	
Fixing mode	By 8 nuts by 4 L brackets	
Front material	Stainless steel 304	
Enclosure Material	PPT	
Type of cooling	Natural convection	
Width	8.41 ln (213.5 mm)	
Height	7.13 ln (181 mm)	
Depth	2.34 ln (59.5 mm)	
Product Weight	2.65 Lb(US) (1.2 kg)	
Environment		
Standards	IEC 61000-6-2	
	EN 61131-2	
Dead of Ond'S and	UL 508	
Product Certifications	CE KCC	
	CULus	
	C-tick	
Ambient Air Temperature for Operation	32131 °F (055 °C)	
Ambient air temperature for storage	-4140 °F (-2060 °C)	
Relative humidity	1090 % without condensation	
Operating altitude	< 6561.68 ft (2000 m)	
IP degree of protection	IP20 IEC 60529 rear panel) IP65 IEC 60529 front panel)	
NEMA degree of protection	NEMA 4X front panel (indoor use)	
Shock resistance	147 m/s² 3 chocks in each direction X, Y and Z EN/IEC 61131-2	
Vibration resistance	3.5 mm 59 Hz) - X, Y, Z directions for 10 cycles (approx. 100 min) - EN/IEC 61131-2 1 gn 9150 Hz) - X, Y, Z directions for 10 cycles (approx. 100 min) - EN/IEC 61131-2	
Resistance to electrostatic discharge	6 KV contact discharge IEC 61000-4-2 level 3	



## Ordering and shipping details

Category	22569 - MAGELIS XBT-GT (AND XBT-G)
Discount Schedule	MC2
GTIN	3606480841781
Nbr. of units in pkg.	1
Package weight(Lbs)	3.98 Lb(US) (1.806 kg)
Returnability	No
Country of origin	CN

### Packing Units

Unit Type of Package 1	PCE	
Package 1 Height	5.71 In (14.5 cm)	
Package 1 width	10.43 ln (26.5 cm)	
Package 1 Length	11.81 ln (30 cm)	
Unit Type of Package 2	S03	
Number of Units in Package 2	4	
Package 2 Weight	15.93 Lb(US) (7.224 kg)	
Package 2 Height	11.81 ln (30 cm)	
Package 2 width	11.81 ln (30 cm)	
Package 2 Length	15.75 ln (40 cm)	

Product Life Status : Commercialised



## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: HMIGTO2315FW