Product data sheet Characteristics

PTEL2R

APC Surge Module for Analog Phone Line, Replaceable, 1U, use with PRM4 or PRM24 Rackmount Chassis







U	ve	rv	ıe	w
_	• •		. •	•••

Lead time	Usually in Stock

General

Provided equipment	User manual

Physical

Color	Black	
Depth	2.72 ln (6.9 cm)	
Height	1.73 ln (4.4 cm)	
Product Weight	0.04 Lb(US) (0.02 kg)	
Width	0.75 ln (1.9 cm)	

Output

Number of power socket outlets	1

Conformance

Product Certifications	CUL Recognized CE
Standards	UL 497A

Environmental

Storage altitude	010000 Ft (0.003048.00 m)	
Storage Relative Humidity	095 %	
Ambient Air Temperature for Storage	5113 °F (-1545 °C)	
Operating altitude	010000 ft	
Relative Humidity	095 %	
Ambient Air Temperature for Operation	5113 °F (-1545 °C)	

Surge Protection and Filtering

Data Lines Protected (multi-line only)	Dual analog line (4 wire)
NM Surge Response Time (ns)	1 ns common mode
Peak current	0.25 KA common mode 0.2 KA normal mode
Data line protection	Analog phone line for phone/fax/modem/DSL (RJ45 connector)

Ordering and shipping details

GTIN	00731304202851
Package weight(Lbs)	0.11 Lb(US) (0.05 kg)

Packing Units

. doming office	
Package 1 Height	3.90 In (9.9 cm)
Package 1 width	1.30 ln (3.3 cm)
Package 1 Length	3.74 In (9.5 cm)
SCC14	30731304202852
Number of Units in Package 2	96
Package 2 Weight	14.77 Lb(US) (6.70 kg)
Package 2 Height	8.125 ln (206.38 mm)
Package 2 width	16.25 ln (412.75 mm)
Package 2 Length	25.125 ln (638.18 mm)
Number of Units in Package 3	28

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
REACh free of SVHC	Yes
EU RoHS Directive	Compliant
Lead free	Yes
WEEE	The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.
Take-back	Take-back program available

Contractual warranty

Warranty	Litetime
· varianty	Endunio

Product Life Status:	Commercialised	



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: PTEL2R