



Main

Range	TeSys
Product or component type	Contacteur coil
Range compatibility	TeSys LC1B contactor TeSys CR1B contactor
Control circuit type	DC AC
Coil type	Low consumption
[Uc] control circuit voltage	110...125 V DC 120...127 V AC 50...400 Hz


Complementary

Control circuit voltage limits	69...79 V
Average resistance	11.4 Ohm
Inrush power in VA	1100...1300 VA 3P 1300...1600 VA 4P 450...620 VA 1P 720...1000 VA 2P
Inrush power in W	1100...1400 W for 4P 380...520 W for 1P 600...800 W for 2P 900...1100 W for 3P
Hold-in power consumption in VA	0.15...0.2 VA 50...400 Hz 1P 0.35...0.5 VA 50...400 Hz 2P 0.7...1 VA 50...400 Hz 3P 1.2...1.6 VA 50...400 Hz 4P
Hold-in power consumption in W	0.15...0.2 W for 1P 0.35...0.5 W for 2P 0.7...1 W for 3P 1.2...1.6 W for 4P
Operating time	25 ms sealed
Mechanical durability	1200000 cycles
Operating rate	<= 120 cyc/mn at <= 131 °F (55 °C)
Product weight	2.47 lb(US) (1.12 kg)

Ordering and shipping details

Category	18074 - SPARE PARTS DISCOUNT I11
Discount Schedule	I11
GTIN	003389110479409
Nbr. of units in pkg.	1
Package weight(Lbs)	2.4900000000000002
Returnability	N
Country of origin	FR

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0801 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including:
- - - - - Substance 1	Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.
- - - - - More information	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period	18 months
-----------------	-----------

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Schneider Electric:](#)

[WB1KB121](#)