# XKBZ992

# contacts blk w simple hdl or zero (center) position interlocking hdl - for XKB



| Main  |  |
|---|--|
| Product or Component<br>Type                      | Controllers separate parts   |
| Accessory / separate part category                | Control accessory  |
| Product Specific Application                      | Light hoisting applications  |
| Product Compatibility                             | XKB  |
| Accessory / Separate<br>Part Type                 | Contacts block   |
| Accessory / separate part specific characteristic | For use with zero (center) position interlocking handle For use with simple handle |

| $\sim$ |    |     |     |      |
|--------|----|-----|-----|------|
| Cin    | mn | lem | ıen | tarv |

| Contact block per direction [control circuit] | 4 per movement   |
|---|--|
| •   | 1 zero (center) position   |
|   | 2 zero per movement  |
| Electrical connection                         | Screw clamp terminal 1 x 0.51 x 1.5 mm <sup>2</sup>                |
|   | Screw clamp terminal 1 x 0.51 x 2.5 mm <sup>2</sup>                |
| Enclosure/cubicle description                 | Monobloc   |
| Contacts type and composition                 | 8 NO   |
|   | 1 NC   |
|   | 2 NC   |
| Contact operation                             | Double-break   |
|   | Slow-break   |
| [Ith] conventional free air thermal current   | 10 A IEC 337-1   |
|   | 10 A NF C 63-140   |
|   | 10 A VDE 0660  |
|   | 10 A CSA C22.2 No 14   |
| [Ui] rated insulation voltage                 | 500 V AC/DC IEC 158-1  |
|   | 500 V AC/DC NF C 20-040  |
|   | 500 V AC/DC VDE 0110   |
| Maximum resistance across terminals           | 25 mOhm 1 A NF C 93-050  |
| Positive opening                              | With   |
| Short-circuit protection                      | 10 A cartridge fuse gG IEC 337-1B                                  |
|   | 10 A cartridge fuse gG VDE 0660 part 2                             |
| Electrical durability                         | 1000000 Cycles DC inductive 120 V 75 IEC 337-1 DC-11 60 cyc/mn 0.5 |
|   | 1000000 Cycles DC inductive 24 V 90 IEC 337-1 DC-11 60 cyc/mn 0.5  |
|   | 1000000 cycles DC inductive 48 V 90 IEC 337-1 DC-11 60 cyc/mn 0.5  |
| Net Weight                                    | 0.47 lb(US) (0.215 kg)   |

#### Environment

| Standards | CENELEC EN 50013 |
|-----------|------------------|
|           |                  |

#### Ordering and shipping details

| Category              | 22474-PUSHBUTTON, CRANE JOYSTICKS |  |
|-----------------------|-----------------------------------|--|
| Discount Schedule     | I                                 |  |
| GTIN                  | 3389110929522                     |  |
| Nbr. of units in pkg. | 1                                 |  |
| Package weight(Lbs)   | 7.19 oz (203.9 g)                 |  |
| Returnability         | No                                |  |
| Country of origin     | FR                                |  |
|                       |                                   |  |

## Packing Units

| •                            |                        |
|------------------------------|------------------------|
| Unit Type of Package 1       | PCE                    |
| Package 1 Height             | 1.38 in (3.5 cm)       |
| Package 1 width              | 4.02 in (10.2 cm)      |
| Package 1 Length             | 4.06 in (10.3 cm)      |
| Unit Type of Package 2       | S01                    |
| Number of Units in Package 2 | 10                     |
| Package 2 Weight             | 4.94 lb(US) (2.241 kg) |
| Package 2 Height             | 5.91 in (15 cm)        |
| Package 2 width              | 5.91 in (15 cm)        |
| Package 2 Length             | 15.75 in (40 cm)       |
| Package 3 Height             | 5.91 in (15 cm)        |
|                              |                        |

## Offer Sustainability

| California proposition 65  | WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov |
|----------------------------|---|
| EU RoHS Directive          | Pro-active compliance (Product out of EU RoHS legal scope)  |
| Mercury free               | Yes   |
| RoHS exemption information | ₫Yes  |
| China RoHS Regulation      | China RoHS Declaration  |
| WEEE                       | The product must be disposed on European Union markets following specific waste collection and never end up in rubbish bins.  |

#### Contractual warranty

| Warranty | 18 months |
|----------|-----------|

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: XKBZ992