AP9600 SMARTSLOT EXPANSION CHASSIS







Overview

Presentation	UPS management accessory that provides additional SmartSlot interface to your APC SmartSlot UPS.
Lead time	Usually in Stock

Main

Number of cables	1
Provided Equipment	User Manual Mounting pads

Physical

Color	Beige	
Height	2.52 in (6.4 cm)	
Width	5.00 in (12.7 cm)	·
Depth	5.24 in (13.3 cm)	
Net Weight	2.01 lb(US) (0.91 kg)	
Mounting Location	Front	
Mounting preference	No preference	
Mounting Mode	Not rack-mountable	

Conformance

Standards	EN 55022 Class B FCC Part 15 class B
Product Certifications	C-tick CE DOC/Industry Cananda VCCI

Environmental

Ambient Air Temperature for Operation	32104 °F (040 °C)	
Operating altitude	010000 ft	
Relative Humidity	095 %	
Ambient Air Temperature for Storage	5149 °F (-1565 °C)	
Storage altitude	050000 ft (0.0015240.00 m)	
Storage Relative Humidity	095 %	

Ordering and shipping details

GTIN	731304002628	
Nbr. of units in pkg.	1	
Package weight(Lbs)	2.51 lb(US) (1.138 kg)	

Packing Units

•	
Unit Type of Package 1	PCE
Package 1 Height	3.15 in (8 cm)
Package 1 width	9.25 in (23.5 cm)
Package 1 Length	5.63 in (14.3 cm)
Unit Type of Package 2	PAL
Number of Units in Package 2	60
Package 2 Weight	150.80 lb(US) (68.4 kg)
Package 2 Height	56.69 in (143.99 cm)
Package 2 width	39.37 in (100 cm)
Package 2 Length	47.24 in (120 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACh Regulation	☑ REACh Declaration
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EVEL RoHS Declaration
Lead free	Yes
Mercury free	Yes
RoHS exemption information	₫ _{Yes}
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

Contractual warranty

Warranty	2 years repair or replace

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric:

AP9600