XZCC20FCM30B

female, 1/2 20UNF, 3-pin, elbowed connector - cable gland Pg 7

Product availability: Non-Stock - Not normally stocked in distribution facility







Cabling accessories
Connector
Elbowed female connector 1/2 20 UNF, 3 pins
Metal
Without
Screw terminal / wire size <= 0.75 mm² / clamping capacity 0.120.24 in (36 mm)

Complementary

Complementary		
Cable gland type	Pg 7	
Cable connector fixing	Screw-on	
System Voltage	250 V AC	
Line Rated Current	4 A	
Enclosure material	Plastic	
Insulating resistance	> 1000 GΩ	
Contact resistance	<= 8000 μOhm	
Product weight	0.04 lb(US) (0.02 kg)	

Environment

IP degree of protection	IP67
Ambient air temperature for operation	-40185 °F (-4085 °C)

Ordering and shipping details

Category	22483 - MACHINE CABLES
Discount Schedule	DS3
GTIN	00785901400493
Nbr. of units in pkg.	1
Package weight(Lbs)	5.9999999999998E-2
Returnability	N
Country of origin	CZ

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0545 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
California proposition 65	WARNING: This product can expose you to chemicals including:
Substance 1	Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
Substance 2	Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
More information	For more information go to www.p65warnings.ca.gov


Warranty period

18 months

Product data sheet Dimensions Drawings

XZCC20FCM30B

Dimensions



(1) Cable gland : no. 7 plastic (Pg 7)

Product data sheet Connections and Schema

XZCC20FCM30B

Connections and Schemes



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: XZCC20FCM30B