## XZCP1169L10

pre-wired connectors XZ - straight female - M12 - 4 pins - cable PUR 10m



Product availability: Non-Stock - Not normally stocked in distribution facility



Main	
Accessory / separate part category	Cabling accessory
Accessory / separate part type	Pre-wired connectors
Series name	General purpose

Comr	olemen	tarv
COITIN	лспісп	tai y

aight female connector

#### Environment

Environment.	
IP degree of protection	IP65 IP67 IP69K
Product certifications	cULus
Ambient air temperature for operation	-40176 °F (-4080 °C) (static) 23176 °F (-580 °C) (flexing)
Ambient air temperature for storage	-40176 °F (-4080 °C)

### Ordering and shipping details

Category	22483 - MACHINE CABLES	
Discount Schedule	DS3	
GTIN	003389110763096	
Nbr. of units in pkg.	1	
Package weight(Lbs)	1.07000000000001	
Returnability	N	
Country of origin	CZ	


### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 0649 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available
California proposition 65	WARNING: This product can expose you to chemicals including:
Substance 1	Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
Substance 2	Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
More information	For more information go to www.p65warnings.ca.gov

#### Contractual warranty

14/	40
Warranty period	18 months

### **Dimensions**




L: Lenght of cable

### Product data sheet Connections and Schema

## XZCP1169L10

### Connections and Schemes

### Connector



BU : Blue BN : Brown BK : Black

Y/G: Yellow / Green

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: XZCP1169L10