## XZCPA1865L10

pre-wired connectors XZ - straight female - 1/2"20 UNF - 3 pins - cable PVC 10m

Product availability: Non-Stock - Not normally stocked in distribution facility



| Main                               |                      |
|------------------------------------|----------------------|
| Accessory / separate part category | Cabling accessory    |
| Accessory / separate part type     | Pre-wired connectors |
| Series name                        | Application          |

Complementary

| Electrical connection    | 1/2"20 UNF, 3 pins straight female connector |  |
|--------------------------|--|--|
| Cable connector fixing   | Screw-on                                     |  |
| Collar material          | Stainless steel 316L                         |  |
| Status LED               | Without                                      |  |
| Cable length             | 32.81 ft (10 m)                              |  |
| Cable outer diameter     | 0.2 in (5 mm)                                |  |
| Cable composition        | 3 x 0.34 mm²                                 |  |
| Wire insulation material | PVC  |  |
| System Voltage           | 250 V AC<br>300 V DC                         |  |
| Line Rated Current       | 4 A  |  |
| Contact resistance       | 5000 μOhm                                    |  |
| Insulating resistance    | 1 GΩ   |  |
| Product weight           | 0.88 lb(US) (0.4 kg)                         |  |
|                          |  |  |

### Environment

| IP degree of protection               | IP69K                         |
|---------------------------------------|-------------------------------|
| Ambient air temperature for operation | -13185 °F (-2585 °C) (static) |
| Ambient air temperature for storage   | -31212 °F (-35100 °C)         |

#### Ordering and shipping details

| Category              | 22483 - MACHINE CABLES |  |
|-----------------------|------------------------|--|
| Discount Schedule     | DS3                    |  |
| GTIN                  | 003389119021623        |  |
| Nbr. of units in pkg. | 1                      |  |
| Package weight(Lbs)   | 0.8000000000000004     |  |
| Returnability         | N                      |  |
| Country of origin     | PL                     |  |
|                       |                        |  |


### Offer Sustainability

| RoHS (date code: YYWW)    | Compliant - since 0601 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity         |  |
|---------------------------|--|--|
| California proposition 65 | WARNING: This product can expose you to chemicals including:   |  |
| Substance 1               | Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and                                |  |
| Substance 2               | Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm. |  |
| More information          | For more information go to www.p65warnings.ca.gov  |  |

#### Contractual warranty

|                  | •         |
|------------------|-----------|
| Managhuasia      | 40        |
| vvarranty period | 18 months |
| * '              |           |

### **Dimensions**



L: Lenght of cable

## Product data sheet Connections and Schema

# XZCPA1865L10

### Connections and Schemes

### Connectors GN

GN: Green RD/ Red/White WH:

RD/ Red / Black

BK:

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: XZCPA1865L10