### XZCPV1141L2

pre-wired connectors XZ - straight female - M12 - 4 pins - cable PVC 2m

Product availability: Stock - Normally stocked in distribution facility



Main	
Accessory / separate part category	Cabling accessory
Accessory / separate part type	Pre-wired connectors
Series name	General purpose

Complementary

o o mpromontary		
Electrical connection	M12, 4 pins straight female connector	
Cable connector fixing	Screw-on	
Collar material	Metal	
Status LED	Without	
Cable length	6.56 ft (2 m)	
Cable outer diameter	0.18 in (4.6 mm)	
Cable composition	4 x 0.25 mm²	
Wire insulation material	PVC	
System Voltage	250 V AC 300 V DC	
Line Rated Current	3 A	
Contact resistance	5000 μOhm	
Insulating resistance	1 GΩ	
Product weight	0.2 lb(US) (0.09 kg)	
-		

#### Environment

IP degree of protection	IP65 IP67	
Product certifications	cULus	
Ambient air temperature for operation	-13176 °F (-2580 °C) (static)	
Ambient air temperature for storage	-13176 °F (-2580 °C)	

#### Ordering and shipping details

S3 1785901457268
785901457268
19


### Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 1201 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
California proposition 65	WARNING: This product can expose you to chemicals including:
Substance 1	Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
Substance 2	Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
More information	For more information go to www.p65warnings.ca.gov

### Contractual warranty

Warranty period	18 months

### **Dimensions**




L: Lenght of cable

### Product data sheet Connections and Schema

## XZCPV1141L2

### Connections and Schemes

### Connector



BN: Brown BK: Black BU: Blue WH: White

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: XZCPV1141L2