## XVCTL1

# 40mm tower light - 3 LED red, amber, green - 24V AC/DC

Product availability: Stock - Normally stocked in distribution facility



Main	
Product or component type	Complete pre-wired monolithic tower light
Beacon or indicator bank unit type	3 illuminated units
Sound signalling	Buzzer
Mounting diameter	1.57 in (40 mm)
Device short name	XVC
Light source	Green LED steady or flashing Orange LED steady or flashing Red LED steady or flashing
Supply circuit type	AC/DC

Complementary

Material	Polycarbonate (illuminated unit)	
	ABS (acrylonitrile butadiene-styrene) (base unit)	
	PBT + ABS (UL94-V0) (top cover)	
	SGP (chromium-plated) (support tube)	
Mounting location	On support tube, 17 mm	
[Us] rated supply voltage	24 V	
Cable cross section	0 in² (0.83 mm²)	
	0 in² (0.33 mm²)	
AWG gauge	AWG 22	
	AWG 18	
Cable length	17.72 in (450 mm)	
Marking	CE	
[Uimp] rated impulse withstand voltage	4 kV	
Flashing frequency	1 Hz	

#### Environment

Standards	EN/IEC 60947-1
	EN/IEC 60947-5-1
Product certifications	UL
Protective treatment	TC
Ambient air temperature for storage	-31158 °F (-3570 °C)
Ambient air temperature for operation	14122 °F (-1050 °C)
Overvoltage category	Class I EN/IEC 61140
IP degree of protection	IP23 in vertical surface installation conforming to EN/IEC 60529
	IP54 in flat surface installation conforming to EN/IEC 60529

#### Ordering and shipping details

Category	22750 - INDUSTRIAL POINT OF PURCHASE
Discount Schedule	IPOP
GTIN	00785901557234
Nbr. of units in pkg.	1
Package weight(Lbs)	0.510000000000001
Returnability	Υ
Country of origin	MX

### Offer Sustainability

California proposition 65	WARNING: This product can expose you to chemicals including:
Substance 1	Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.
More information	For more information go to www.p65warnings.ca.gov

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: XVCTL1