Product data sheet Characteristics

9001KM55LR PUSH BUTTON LIGHT MODULE 30MMT-K +SK+KX

Product availability: Non-Stock - Not normally stocked in distribution facility



Main	
Range of product	Harmony 9001SK Harmony 9001K
Product or component type	Light block
Device short name	9001K
Light block supply	Direct

Complementary

Product weight	0.25 lb(US) (0.115 kg)
Light source	LED
Light block colour	Red
[Us] rated supply voltage	2428 V AC/DC

Environment

- ·		
Protective treatment	TC	
Ambient air temperature for storage	-40158 °F (-4070 °C)	_
Ambient air temperature for operation	-13158 °F (-2570 °C)	
IP degree of protection	IP20 conforming to IEC 60529	
Standards	JIS C 852 EN/IEC 60947-1 EN/IEC 60947-5-1 UL 508 EN/IEC 60947-5-4 CSA C22.2 No 14 JIS C 4520	
Product certifications	NEMA UL 508	
Electrical shock protection class	Class II conforming to IEC 61140	
Vibration resistance	7 gn (f = 2500 Hz) conforming to IEC 60068-2-6	
Shock resistance	50 gn conforming to IEC 60068-2-27	

Ordering and shipping details

Category	21435 - 9001 KM LIGHT MODULES
Discount Schedule	CS1
GTIN	00785901771432
Nbr. of units in pkg.	1
Package weight(Lbs)	0.25
Returnability	N
Country of origin	MX

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0921 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including:
Substance 1	Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm.
More information	For more information go to www.p65warnings.ca.gov


Contractual warranty

Warranty period	18 months

Product data sheet Dimensions Drawings

9001KM55LR

Dimensions



e panel thickness: 1 to 6 mm / 0.04 to 0.24 in.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: 9001KM55LR