Product data sheet Characteristics

ZB4AEQ4035

red Ø40 Emerg switching off button + contact block NC + light block 12V



Product availability: Non-Stock - Not normally stocked in distribution facility

| NΛ | 21 | m |
|----|----|---|

| Range of product | Harmony XB4 |
|-------------------------------|------------------------------------|
| Product or component type | Kit for emergency stop push-button |
| Device short name | ZB4 |
| Bezel material | Chromium plated metal |
| Head type | Standard |
| Sale per indivisible quantity | 1 |
| Shape of signaling unit head | Round |
| Type of operator | Mechanical latching |
| Reset | Push-pull |
| Operator profile | Red mushroom Ø 40 mm |

Complementary

| CAD overall width | 1.57 in (40 mm) | |
|------------------------------------|---|--|
| CAD overall height | 1.85 in (47 mm) | |
| CAD overall depth | 3.27 in (83 mm) | |
| Product weight | 0.29 lb(US) (0.13 kg) | |
| Resistance to high pressure washer | 1015.26 psi (7000000 Pa) at 131 °F (55 °C),distance: 0.1 m | |
| Kit composition | 1 mushroom head emergency stop push-button 1 contact block - NC contact 1 LED lamp 12 V | |
| Mechanical durability | 300000 cycles | |
| | | |

Environment

| Environment | |
|---------------------------------------|---|
| Protective treatment | TH |
| Ambient air temperature for storage | -40158 °F (-4070 °C) |
| Ambient air temperature for operation | -13158 °F (-2570 °C) |
| Overvoltage category | Class I conforming to IEC 60536 |
| IP degree of protection | IP66 conforming to IEC 60529 |
| NEMA degree of protection | NEMA 13 NEMA 4X |
| IK degree of protection | IK05 conforming to EN 50102 |
| Standards | EN/IEC 60947-1 EN/IEC 60947-5-1 EN/IEC 60947-5-4 EN/IEC 60947-5-5 IEC 60364-5-53 JIS C 4520 UL 508 CSA C22.2 No 14 |
| Product certifications | BV CSA DNV GL LROS (Lloyds register of shipping) RINA UL listed |

| Vibration resistance | 5 gn (f = 2500 Hz) conforming to IEC 60068-2-6 |
|----------------------|---|
| Shock resistance | 30 gn (duration = 18 ms) half sine wave acceleration conforming to IEC 60068-2-27 50 gn (duration = 11 ms) half sine wave acceleration conforming to IEC 60068-2-27 |

Ordering and shipping details

| Category | 22468 - PUSHBUTTONS,22MM(METAL) NEW |
|-----------------------|-------------------------------------|
| Discount Schedule | CS2 |
| GTIN | 003606480507243 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 0.5 |
| Returnability | N |
| Country of origin | FR |

Offer Sustainability

| Sustainable offer status | Green Premium product | |
|----------------------------------|--|--|
| RoHS (date code: YYWW) | Compliant - since 0627 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity | |
| REACh | Reference not containing SVHC above the threshold | |
| Product environmental profile | Available | |
| Product end of life instructions | Need no specific recycling operations | |
| California proposition 65 | WARNING: This product can expose you to chemicals including: | |
| Substance 1 | Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. | |
| More information | For more information go to www.p65warnings.ca.gov | |

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: ZB4AEQ4035