ZB4BG4K1312A

key selector switch head Ø22 2 position - 1312A



Main Range

| Range of Product | Harmony XB4 |
|-------------------------------|------------------------------|
| Product or Component Type | Head for key selector switch |
| Device short name | ZB4 |
| Bezel material | Chromium plated metal |
| Mounting diameter | 0.87 in (22 mm) |
| Sale per indivisible quantity | 1 |
| Shape of signaling unit head | Round |
| Operator profile | Black key switch |
| Operator position information | 2 positions 90° |
| Type of Keylock | Ronis 1312A |
| Product compatibility | 4 multi-chip |
| Key withdrawal position | In any position |

Complementary

| Device presentation | Basic element | · |
|------------------------------------|---|---|
| | C15 1 single front mounting | |
| | C11 3 single front mounting | |
| | C8 4 single and double front mounting | |
| | C7 4 single front mounting | |
| | C6 5 single and double front mounting | |
| | C5 5 single front mounting | |
| · | C4 6 single and double front mounting | |
| Electrical composition code | C3 6 single front mounting | |
| Mechanical durability | 1000000 cycles | |
| Resistance to high pressure washer | 1015.26 psi (7000000 Pa) 131 °F (55 °C) 0.1 m | |
| CAD overall depth | 2.83 in (72 mm) | |
| CAD overall height | 1.14 in (29 mm) | |
| | , , | |
| CAD overall width | 1.14 in (29 mm) | |

Environment

| Environment | |
|---------------------------------------|---|
| Protective treatment | ТН |
| Ambient Air Temperature for Storage | -40158 °F (-4070 °C) |
| Ambient air temperature for operation | -13158 °F (-2570 °C) |
| Overvoltage category | Class I IEC 60536 |
| IP degree of protection | IP69K IEC 60529 |
| NEMA degree of protection | NEMA 13 NEMA 4X |
| Standards | EN/IEC 60947-5-5 UL 508 CSA C22.2 No 14 EN/IEC 60947-5-1 GB 14048.5 EN/IEC 60947-5-4 EN/IEC 60947-1 |
| Product Certifications | LROS (Lloyds register of shipping) CSA UL Listed GL BV DNV |

| Vibration resistance | 5 gn 2500 Hz)IEC 60068-2-6 |
|----------------------|--|
| Shock resistance | 30 gn 18 ms) half sine wave acceleration IEC 60068-2-27 50 gn 11 ms) half sine wave acceleration IEC 60068-2-27 |

Ordering and shipping details

| 0 11 0 | |
|-----------------------|-------------------------------------|
| Category | 22468 - PUSHBUTTONS,22MM(METAL) NEW |
| Discount Schedule | CS2 |
| GTIN | 00785901933854 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 0.15 lb(US) (0.07 kg) |
| Returnability | No |
| Country of origin | FR |
| | |

Contractual warranty

| Warranty | 18 months |
|----------|-----------|
|----------|-----------|

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: ZB4BG4K1312A