


Product availability: Non-Stock - Not normally stocked in distribution facility



Main

Range of product	Preventa Safety detection
Accessory / separate part category	Mounting and fixing accessories
Accessory / separate part type	Fixing column
Offer type	Without mirror
Product compatibility	XUSL.E...151 to XUSL.E...181
Accessory / separate part destination	Safety light curtain type 2 Safety light curtain type 4


Complementary

Ambient air temperature for operation	14...121 °F 14...122 °F (-10...50 °C)
Ambient air temperature for storage	-13...158 °F (-25...70 °C) -13...158 °F
Column height	77.56 in (1970 mm)
Height protected	71.26 in (1810 mm)
Product weight	13.23 lb(US) (6 kg)

Ordering and shipping details


Category	22455 - LIGHT CURTAINS - XUSL
Discount Schedule	DS2
GTIN	003389119619226
Nbr. of units in pkg.	1
Package weight(Lbs)	0.01
Returnability	N
Country of origin	IT

Offer Sustainability


Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1425 - Schneider Electric declaration of conformity  Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available
California proposition 65	WARNING: This product can expose you to chemicals including:
- - - - - Substance 1	Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
- - - - - Substance 2	Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
- - - - - More information	For more information go to www.p65warnings.ca.gov

Dimensions


With XUSZFB2



With XUSZFB1



Mounting and Clearance



Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Schneider Electric:](#)

[XUSZSC202](#)