



## Overview

Presentation	Intelligent and efficient network power protection from entry level to scalable runtime. Ideal UPS for servers, point-of-sale, routers, switches, hubs and other network devices.
Lead time	Usually in Stock

## Main

Kw Rating	500 W
Rated power in VA	750 VA
Nb of power socket outlets	6 NEMA 5-15R
Main Output Voltage	120 V
Main Input Voltage	120 V
Plug standard	NEMA 5-15P
Cable length	6 ft (1.83 m)
Number of cables	1

## General

Number of power module filled slots	0
Number of power module free slots	0
Redundant	No
Provided equipment	CD with software Documentation CD USB cable

## Physical

Mounting Location	Front
Mounting Mode	Not rack-mountable
Mounting preference	No preference
Depth	14.29 in (36.3 cm)
Height	6.34 in (16.1 cm)
Net Weight	29.06 lb(US) (13.18 kg)
Width	5.43 in (13.8 cm)
Two post mountable	0
USB compatible	Yes
Color	Black

## Input

Efficiency at full load	75...154 V adjustable 82...144 V
Input Frequency	50/60 Hz +/- 3 Hz auto-sensing

## Output

Harmonic distortion	Less than 5%
Maximum configurable power in VA	750 VA
Max Configurable Power (Watts)	500 W
Transfer Time	4ms typical : 8ms maximum
Topology	Line Interactive
Waveform Type	Sine wave
Output Frequency (sync to mains)	50/60 Hz +/- 3 Hz sync to mains

## Conformance

Product Certifications	CSA
Equipment protection policy	Lifetime : \$150000
Standards	UL 1778

## Environmental

Acoustic level	40 dBA
Heat dissipation	90 Btu/h
Operating altitude	0...10000 ft
Ambient air temperature for operation	32...104 °F (0...40 °C)
Ambient Air Temperature for Storage	5...113 °F (-15...45 °C)
Storage altitude	0...50000 ft (0.00...15240.00 m)
Relative Humidity	0...95 %
Storage Relative Humidity	0...95 %

## Batteries & Runtime

Battery Type	Lead-Acid battery
Battery Voltage	24 V
Extendable Run Time	0
Battery Capacity	7.0 Ah
Included Battery Modules	0
Battery Slots Empty	0
Typical recharge time	3 h
RBC Quantity	1
Battery life	3...5 year(s)
Battery power in VAh	146 VAh runtime
Battery Charge Power (Watts)	49 W rated

## Communications & Management

Audible Alarm	Alarm when on battery : distinctive low battery alarm : configurable delays
Control panel	Multi-function LCD status and control console
Emergency Power Off (EPO)	Optional
Free slots	1

## Surge Protection and Filtering

Surge energy rating	540 J
Filtering	Full time multi-pole noise filtering : 0.3% IEEE surge let-through : zero clamping response time : m

### Ordering and shipping details

Category	11309 - APC RESALE PRODUCTS
Nbr. of units in pkg.	1
Package weight(Lbs)	1 lb(US) (0.45 kg)
Returnability	No
Country of origin	PH

### Packing Units

Package 1 Height	11.85 in (30.1 cm)
Package 1 width	10.94 in (27.8 cm)
Package 1 Length	19.65 in (49.9 cm)
SCC14	0
Number of Units in Package 3	24

### Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	<a href="#">REACH Declaration</a>
EU RoHS Directive	Compliant <a href="#">EU RoHS Declaration</a>
Mercury free	Yes
RoHS exemption information	<a href="#">Yes</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
Circularity Profile	<a href="#">End Of Life Information</a>
Optimized Energy Efficiency	Energy efficient product
Take-back	Take-back program available

### Contractual warranty

Warranty	3 years repair or replace (excluding battery) and 2 years for battery
----------	---

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Schneider Electric:](#)

[SMT750](#)