Product datasheet Characteristics

XCSA713FW1

Device short name	XCSA
Enclosure type	Enclosure corrosion resistance indoor/outdoor Enclosure dust and damp proof indoor/outdoor

Complementary

Line Rated Current	10 A
Actuator	Key
Contact operation	Slow-break, break before make
Contacts type and composition	1 NO/2 NC
Depth	1.73 in
Enclosure material	Metal
Height	4.47 in
Locking options description	Without locking of actuator
Number of poles	3
Permissible voltage	<= 300 V AC
Pilot light	LED orange 24/48 V

Environment

ambient air temperature for operation	-13158 °F	
IP degree of protection	IP67	
NEMA degree of protection	NEMA 4/4X/12	

Offer Sustainability

WARNING: This product can expose you to chemicals	WARNING: This product can expose you to chemicals including:		
including:			
Dijsononyl ohthalate (DINP), which is known to the State Dijsononyl ohthalate (DINP), which is known to the State of California to cause			

Di-isodecyl phthalate (DIDP), which is known to the State Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth of California to cause birth defects or other reproductive defects or other reproductive harm.

For more information go to www.p65warnings.ca.gov For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period	18 months
-----------------	-----------

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric: XCSA713FW1