XCCRAR1214

shaft coupling - for encoder - with spring \varnothing 12 to 14 mm

Product availability: Non-Stock - Not normally stocked in distribution facility



Main	
Product or component type	Shaft coupling
Accessory / separate part destination	Rotary encoder with solid shaft
Accessory / separate part category	Coupling accessories
Accessory / separate part type	Spring
Bore diameter encoder side	0.47 in (12 mm)
Bore diameter machine side	0.55 in (14 mm)
Compression expansion	+/- 1 mm

Complementary

Collar material	Zamak
Spring material	Nickel plated steel
Maximum angular misalignment	5°
Maximum radial misalignment	+/- 1.5 mm
Torque value	<= 26.55 lbf.in (3 N.m)
Product weight	0.23 lb(US) (0.105 kg)

Ordering and shipping details

Category	21581 - ENCODERS, XCC	
Discount Schedule	DS2	
GTIN	003389110935752	
Nbr. of units in pkg.	1	
Package weight(Lbs)	0.25	
Returnability	N	
Country of origin	FR	

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0701 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACh	Reference not containing SVHC above the threshold
California proposition 65	WARNING: This product can expose you to chemicals including:
Substance 1	Diisononyl phthalate (DINP), which is known to the State of California to cause cancer, and
Substance 2	Di-isodecyl phthalate (DIDP), which is known to the State of California to cause birth defects or other reproductive harm.
More information	For more information go to www.p65warnings.ca.gov


Contractual warranty

	<u> </u>
Warranty period	18 months

Product data sheet Dimensions Drawings

XCCRAR1214

Dimensions



Ø e	Ø s
12 mm	14 mm

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Telemecanique Sensors:

XCCRAR1214