

Product availability: Non-Stock - Not normally stocked in distribution facility



Main

Range	TeSys
Product or component type	Shunt trip
Device short name	GV7AS
Device application	Control
Range compatibility	TeSys TeSys GV7 TeSys TeSys GV5 TeSys TeSys GV6

Complementary

[Uc] control circuit voltage	110...130 V AC 50/60 Hz
Control circuit voltage limits	0.7...1.1 Un
[Ui] rated insulation voltage	690 V AC conforming to IEC 60947-1 600 V AC conforming to UL 508 600 V AC conforming to CSA C22.2 No 14
Threshold tripping voltage	0.2...0.75 Ue
Inrush power in VA	10 VA for AC network
Hold-in power consumption in VA	5 VA for AC network
Operating time	< 50 ms conforming to IEC 60947-1
On-load factor	100 %
Connections - terminals	Screw clamp terminals 1 cable 1 mm ² - cable stiffness: flexible - with cable end cable end Screw clamp terminals 1 cable 1.5 mm ² - cable stiffness: flexible - without cable end cable end Screw clamp terminals 1 cable 1.5 mm ² - cable stiffness: solid
Tightening torque	1.2 N.m - on screw clamp terminals
Product weight	0.23 lb(US) (0.105 kg)
Quantity per set	Set of 10

Ordering and shipping details

Category	22366 - MAN STR PROTECTORS-GV1/GV3
Discount Schedule	I11
GTIN	00785901566946
Nbr. of units in pkg.	1
Package weight(Lbs)	0.28000000000000003
Returnability	N
Country of origin	FR

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0744 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
California proposition 65	WARNING: This product can expose you to chemicals including:
- - - - - Substance 1	Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer.
- - - - - More information	For more information go to www.p65warnings.ca.gov

Contractual warranty

Warranty period	18 months
-----------------	-----------

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Schneider Electric:](#)

[GV7AS107](#)