GV7AU207

Voltage release, TeSys GV5 GV6 GV7, MN undervoltage trip, 200-240V AC 50/60Hz

Product availability: Non-Stock - Not normally stocked in distribution facility



Main	
Range	TeSys
Product or component type	Undervoltage trip
Device short name	GV7AS
Device application	Control
Range compatibility	TeSys TeSys GV7 TeSys TeSys GV5 TeSys TeSys GV6

Complementary

Complementary	
[Uc] control circuit voltage	200240 V AC 50/60 Hz
Control circuit voltage limits	0.851.1 Un
[Ui] rated insulation voltage	690 V AC conforming to IEC 60947-1 600 V AC conforming to UL 508 600 V AC conforming to CSA C22.2 No 14
Threshold tripping voltage	0.350.7 Ue
Inrush power in VA	10 VA for AC network
Hold-in power consumption in VA	5 VA for AC network
Operating time	< 50 ms conforming to IEC 60947-1
On-load factor	100 %
Connections - terminals	Screw clamp terminals 1 cable 1 mm² - cable stiffness: flexible - with cable end cable end Screw clamp terminals 1 cable 1.5 mm² - cable stiffness: flexible - without cable end cable end Screw clamp terminals 1 cable 1.5 mm² - cable stiffness: solid
Tightening torque	1.2 N.m - on screw clamp terminals
Product weight	0.23 lb(US) (0.105 kg)
Quantity per set	Set of 10

Ordering and shipping details

22366 - MAN STR PROTECTORS-GV1/GV3
l11
00785901566939
1
0.28000000000000003
N
FR

Offer Sustainability

RoHS (date code: YYWW)	Compliant - since 0744 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
California proposition 65	WARNING: This product can expose you to chemicals including:
Substance 1	Antimony oxide & Antimony trioxide, which is known to the State of California to cause cancer.
More information	For more information go to www.p65warnings.ca.gov

Warranty period

18 months

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schneider Electric:

GV7AU207