



Main

Commercial Status	Commercialised
Range of product	Preventa Safety detection
Accessory / separate part designation	IP67 protection tube
Accessory / separate part type	Protection tube
Accessory / separate part category	Protection accessories
Product compatibility	XUSLB...0440 XUSLDM...0440 XUSLDS...0440
Accessory / separate part destination	Safety light curtain type 4
Quantity per set	Set of 2

Complementary

Height	17.48 in (443.9 mm)
Material	Acrylic
Sensing distance reduction coefficient	0.90 Sn
Product weight	7.21 lb(US) (3.27 kg)

Environment

IP degree of protection	IP67 conforming to IEC 60529
Resistance to chemical agents	Inorganic diluted acids Limited resistant against ketones Limited resistant against chlorinated or aromatic hydrocarbons Limited resistant against esters Resistant alkalis Resistant aqueous solutions Resistant aliphatic hydrocarbons Resistant detergents and cleaners
Environmental characteristic	Adverse weather resistant Humidity resistant Resistant against immersion in water UV resistant
Ambient air temperature for operation	32...104 °F (0...40 °C)
Ambient air temperature for storage	-13...158 °F (-25...70 °C)

Ordering and shipping details

Category	22455 - LIGHT CURTAINS - XUSL
Discount Schedule	T
GTIN	00785901660316
Nbr. of units in pkg.	1
Package weight(Lbs)	3.74
Product availability	Non-Stock - Not normally stocked in distribution facility
Returnability	N
Country of origin	US

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS	Compliant - since 0947 - Schneider Electric declaration of conformity

Contractual warranty

Period	18 months
--------	-----------

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Telemecanique Sensors:](#)

[XUSLZD70440](#)