Fuseholder Open Design, 6.3 x 32 mm, THT



# 2.5W / 10A @Tu 23°C · 500 VAC · 16 A (UL)

See below:

**Approvals and Compliances** 

Description - Through hole mounting		<b>Weblinks</b> pdf data sheet, html datasheet, General Product Information, Distributor-Stock-Check, Detailed request for product, Microsite	
Technical Data			
Fuse-Link	6.3 x 32 mm	Soldering Methods	Wave
Mounting	PCB		Soldering Profile
Attachment	Screw/rivet/THT	Solderability	245°C / 3 sec acc. to IEC 60068-2-20,
Terminal	Solder THT		Test Ta, method 1
Rated Voltage	500 VAC (UL)	Resistance to Soldering Heat	260°C / 10 sec acc. to IEC 60068-2-20,
Rated current	16A (UL)		Test Tb, method 1A
Rated Power Acceptance IEC	2.5W / 10A @Tu 23°C	Contact Resistance	≤ 10 mΩ at 100 mA acc. to IEC
Admissible Ambient Temp.	-40 °C to 85 °C		60127-6
Climatic Category	40/085/21 acc. to IEC 60068-1	Dielectric Strength	> 3kV between live parts
Material: Terminals	Copper alloy, tin-plated		(50 Hz: 1 min)
Unit Weight	7.23 q	Impulse Withstand Voltage	> 4 kV between live parts
Storage Conditions	0°C to 60°C, max. 70% r.h.	Insulation Resistance	$> 10  \text{M}\Omega$ between live parts (500 VDC: 1 min)
Product Marking	Rated Voltage, Rated current, Certification marks		

#### **Approvals and Compliances**

Detailed information on product approvals, code requirements, usage instructions and detailed test conditions can be looked up in Details about Approvals

SCHURTER products are designed for use in industrial environments. They have approvals from independent testing bodies according to national and international standards. Products with specific characteristics and requirements such as required in the automotive sector according to IATF 16949, medical technology according to ISO 13485 or in the aerospace industry can be offered exclusively with customer-specific, individual agreements by SCHURTER.

#### **Approvals**

The approval mark is used by the testing authorities to certify compliance with the safety requirements placed on electronic products. Approval Reference Type: OG (Holder) 6.3x32

Approval Logo	Certificates	Certification Body	Description
c <b>FL</b> °us	UL Approvals	UL	UR File Number: E39328

#### **Product standards**

Product standards that are referenced

Organization	Design	Standard	Description
(UL)	Designed according to	UL 4248-1	Industrial Control Equipment
CSA Group	Designed according to	CSA C22.2 no. 4248.1	Industrial Control Equipment

## **Application standards**

Application standards where the product can be used


Organization	Design	Standard	Description
<u>IEC.</u>	Suitable for applications acc.	IEC/UL 62368-1	Audio/video, information and communication technology equipment - Part 1: Safety requirements


#### Compliances

The product complies with following Guide Lines

Identification	Details	Initiator	Description
C€	CE declaration of conformity	SCHURTER AG	The CE marking declares that the product complies with the applicable requirements laid down in the harmonisation of Community legislation on its affixing in accordance with EU Regulation 765/2008.
UK CA	UKCA declaration of conformity	SCHURTER AG	The UKCA marking declares that the product complies with the applicable requirements laid down in the British Amendment of Regulation (EC) 765/2008.
ROHS	RoHS	SCHURTER AG	Directive RoHS 2011/65/EU, Amendment (EU) 2015/863
<b>©</b>	China RoHS	SCHURTER AG	The law SJ / T 11363-2006 (China RoHS) has been in force since 1 March 2007. It is similar to the EU directive RoHS.
REACH	REACH	SCHURTER AG	On 1 June 2007, Regulation (EC) No 1907/2006 on the Registration, Evaluation, Authorization and Restriction of Chemicals 1 (abbreviated as "REACH") entered into force.

## Dimension [mm]






Drilling diagram

## **Derating Curves**

acc. to IEC



## **Variants**

Holder	Order Number
•	0031 8002

Availability for all products can be searched real-time: https://www.schurter.com/en/info-center/support-tools/ stock-check-distributors Packaging Unit Bulk (100 pcs.)

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Schurter:

0031.8002