

## LTPD/CAPD Series 24 V **Printer** Mechanisms



In today's market product designers are asked to deliver smaller devices with more robust functionality, greater longevity, and enhanced reliability. To succeed products must be priced competitively and time to market is key. Point-of-sale (POS) systems, medical devices, and other products with embedded thermal printers are no exception. Each new generation must do more, cost less, and last longer.

New 24 V LTPD and CAPD series thermal printer mechanisms help engineers meet these challenges. These mechanisms are smaller and more robust, offering industry leading value, backed by critical advancements in design flexibility and reliability.

### Small Form Factor

LTPD and CAPD series mechanisms free up critical design real estate. The new mechanisms offer a smaller overall form factor, innovative angled paper guide that requires less depth, and a smaller pitch flexible print circuit (FPC) cable.



### Proven Reliability

LTPD and CAPD models are rated for a minimum of 100 km total printing and 100 million pulses for long life reliability. CAPD models offer a new built-in auto-cutter design, improving cutter reliability. The result: reliable media output, every time.

### Design Flexibility

An array of form factor choices provides more flexibility for a smoother integration process. Options include, ASIC and interface board solutions, and both horizontal and vertical mechanical orientation designs.

- **2" and 3" print width models**
- **Choice of horizontal and vertical orientations**
- **EZ-OP clamshell paper replacement**
- **Platen latch for better shock absorption**
- **Available built-in auto-cutter (CAPD models)**



2" vertical LTPD model and 2" CAPD model.

## Product Specifications

Model	LTPD247	LTPD347	CAPD247	CAPD347
Printing	Thermal line dot printing			
	Method			
	Number of dots/line	432	576	432
	Resolution(dots/mm)		8	
	Paper width (mm)	58 <sup>+0.1</sup>	80 <sup>+0.1</sup>	58 <sup>+0.1</sup>
	Printing width (mm)	54	72	54
Sensors	Speed (max mm/sec)	200	170	200
	Paper path	Curved		
	Head temperature	By thermistor		
	Platen position detection	By mechanical switch		
	Out of paper detection	By photo interrupter		
	Cutter home position detection	-	-	By photo interrupter
Power supply (V)	Operating Voltage (Vdd)	2.7 to 3.6 / 4.75 to 5.25		
	Operating Voltage (Vp)	21.6 to 26.4		
Peak current (A)	Head	2.61 (26.4 V/144 dots)	2.61 (26.4 V/144 dots)	2.61 (26.4V/144dots)
		5.23 (26.4 V/288 dots)	5.23 (26.4 V/288 dots)	5.23 (26.4V/288dots)
	Motor	0.44	0.4	0.44
Service life	Cutter	-	-	0.55
	Pulse activation (pulses)	100 million		
	Abrasion resistance (km)*	100 *		
Operating temperature (°C)		-10 to 50		
		-10 to 50		
Dimensions (W x D x H mm)*	Horizontal	71.0 x 30.0 x 15.0 **	91.0 x 30.0 x 15.0 **	83.1 x 35.4 x 26.9 **
	Vertical	71.0 x 15.0 x 30.0 **	91.0 x 15.0 x 30.0 **	105.1x35.4x27.2***
Mass(g)		Approx. 56	Approx. 64	Approx. 131
				Approx. 154
Auto-cutter	Method	-	-	Slide cutting
	Paper thickness (um)	-	-	54 to 90
	Cutting type	-	-	54 to 78
	Operating time (sec/cycle)	-	-	Full cut and partial cut (1.5±0.5mm tab left at the center)
	Minimum paper cutting length (mm)	-	-	0.5
	Cutting frequency (max cuts/min)	-	-	10
Life span		-	-	30
	Paper cutting (cuts)	-	-	700,000 *

\*Use recommended thermal paper. \*\*Excluding convex section.

\*\*\*Excluding Mounting Part. Specifications are subject to change without notice.

## IF Board Specifications

	IFD001-01UK-E	IFD001-01SK-E
CPU	PTD00P01-E	
Corresponding Model	LTPD247, LTPD347 Series	
Operating Voltage (V)	CAPD247, CAPD347 Series	
Character matrix (H x W dots)	Vp:21.6 to 26.4	
	16 dot characters: 16 x 8, 16 x 16	
	24 dot characters: 24 x 12, 24 x 24	
Character Type	Optional font	Yes
	Downloaded character	Yes
	User-defined character	Yes
	Extend graphics character set	Yes
	Katakana character set	Yes
	Codepage 1252	Yes
Communication interface	JIS 1&2 level kanji	Yes
	USB(2.0)	Serial (RS-232C)
Dimensions (W x D x H mm)	69.0 x 50.0 x 14.0	

## ASIC Specifications:

	PTD00P01-E
Corresponding model	LTPD247, LTPD347 series
Package form	CAPD247, CAPD347 series
Operating voltage (V)	120 pin QFP
Operating frequency (MHz)	Vp:21.6 to 26.4, Vcc:3.0 to 3.6
Configuration	12MHz±0.01%
Communication interface	C-MOS LSI
Character type	Parallel, Serial, USB
	Extended graphics character set
	Other characters available with CGs or external memory
Character matrix (H x W dots)	16 dot characters: 16 x 8, 16 x 16
Dimensions (W x D x H mm)	24 dot characters: 24 x 12, 24 x 24
	16.0 x 16.0 x 1.7

## Optional Cables

Accessory	Product
Power Cable	DC-04100A-E
Switch Cable	OC-D1430A-E
Serial Cable	OC-D0730A-E
USB Cable	IFC-U01-1-E

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## Seiko Instruments:

[IFC-U01-1-E](#) [CAPD247A-E](#) [CAPD347A-E](#) [IFD001-01SK-E](#) [IFD001-01UK-E](#) [LTPD247A-432-E](#) [LTPD247B-432-E](#)  
[LTPD347A-576-E](#) [LTPD347B-576-E](#) [PTD00P01-E](#)