	CURRENT (AMPS)	WORKING VOLTAGE				MANIMUM	MAXIMUM MIN. INSERTION LOSS PER MIL-STD-220,		
CASE FINISH		-55°C TO +85°C		-55°C TO +125°C		MAXIMUM DC RESISTANCE	VOLTAGE DROP	P MINIMUM FULL LOAD, +25°C	
		AC AC	DC	AC AC	DC	(OHMS)	DC AC	(uF)	
SOLDER	3				100	0.05	0.15	1.5 25 51 80 80 80 80 -	
OLSP2 100VD 51-31	M28861/02- 2 DATE CODI DC 3A 11-367	009ТВ <u>Е</u>	[1.27	070 Slot (2X X1.77] 793 M [20.14] 150	()			0.16] 0.407/.397 0/10.33/10.08] 	
MARKING N/A	S NOTES:			SCH • Ţ	[4.83] EMATIO		- 	NOTES: MTG. HARDWARE 1) MOUNTING TORQUE NOT TO EXCEED 7in-lbs. 2) THIS PART CODED "NCA". SCI DOES NOT HAVE CHANGE AUTHORITY. CUSTOMER APPROVAL REQUIRED BEFORE PRODUCT/PROCESS CHANGES CAN BE MADE.	
	Quality					 	57813–ENG (C) 180961 (D) 180961 (TOLERANCES UNLESS OTHERWISE SPECIFIED Fractions ± IMENSIONS ARE IN INCHES. [MILLIMETERS] DO NOT SCALE. TOLERANCES UNLESS OTHERWISE SPECIFIED Fractions ± Decxxx± Dec.	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Spectrum Control: 51-311-367