

CAPACITANCE: Cmax≥70 pF, Cmin≤4.0pF.

2 WORKING VOLTAGE : 10000 VDC.

ы. WITHSTANDING VOLTAGE : 20000 VDC.

4 ⁷⁰ Q ≥ 600 @ 25MHZ

ဖ 00

ROTATIONAL LIFE: 10,000 TURNS DIMENSIONS IN INCHES/MM.

ANGULAR:

DATE:

DRAWING NUMBER

REV. 8

SGNM70-10E

÷

01/08/2018

1/64

SGNMNC70-10E

CONSTRUCTION : 40 psi SEALED, NON-MAGNETIC.

76.

OPERATING TEMPERATURE : -55°C TO 125°C

TORQUE: 0.5 TO 5.0 oz-in.

TOLERANCES: (EXCEPT AS NOTED)

SPRAGUE GOODMAN ELECTRONICS INC. 1700 SHAMES DRIVE WESTBURY, NY 11590

DECIMAL: ±.<u>005 in</u> ±.<u>130 mm</u>

MATERIAL:

SCALE:

DRAWN BY: R. LEVIN APPROVED: I. DITLYA USED FOR:

NONE

FRACTIONAL: | TITLE:

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Sprague Goodman: SGNM70-10E