

SPECIFICATIONS											
Т	OUTPUT						SHAFT		TERMINAL CONNECTIONS		
HERTZ	VOLTS	CONSTANT CURRENT LOAD		CONSTANT IMPEDANCE LOAD		ROTATION TO INCREASE		FOR INCREASING VOLTAGE AS VIEWED FROM BASE END ■			
		MAX. AMPS	MAX. KVA	MAX. AMPS	MAX. KVA	VOLTAGE		INPUT			
50/60	0-240	10	2.4	13	3.12	C۱	V 1-1		4-4	3-3	
						CC	W	4-4	1-1	3-3	
	0-280	10	2.8			C۱	N	5-5	4-4	3-3	
						CC	W	2-2	1-1	3-3	
50/60	0-120	10	2.08	13	2.70	C١	N	1-4-	1 4-4	3-4-3	
						CC	W	4-1-	4 1-1	3-1-3	
	0-140	10	2.42			C۱	N	5-4-	5 4-4	3-4-3	
						CCW		2-1-	2 1-1	3-1-3	
RANCE IS ± DRAFT 1-1/2°	UNITS IN [mm]		PEC.						_ST/	IÇO	
	ALL DIMENSIONS APPLY AFTER PLATING	VARAIBLE TRANS				DOT	rme 2			RGY rs co.	
sed herein was originated by (PRODUCTS CO., which reserves nufacturing, reproduction, use any article disclosed therein expressly granted to others, o vendor proprietary parts.		drawn by S.A. SMITH		DATE FIRST US 9/18/97		ED ON DO I SCALE		NOT 301 (mponents Corporation of Gaddis Boulevard Dayton,		
		CHECKER		DATE WEIGHT A		APPROX.	CAGE 830				
		ENGINEER		DATE SCALE		1 = 1	SHEET 1	OF 1) 031-	-1664	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Staco: 1010BCT-2