

SPECIFICATIONS													
UT	OUTPUT						SHAF	Т	TERMINAL CONNECTIONS				
HERTZ	VOLTS	CONSTANT CURRENT LOAD		CONSTANT IMPEDANCE LOAD			ROTATI TO	ION	FOR INCREASING VOLTAGE AS VIEWED FROM BASE END ■				
		MAX. AMPS	MAX. KVA	MAX. AMPS	MA KV		VOLTAGE		INPL		JUMPER		
60	0-240	12	2.88	15	3.60	30	CW	V 1		1	4-4	3-3	
							CCW		4-4		1-1	3-3	
60	0-120	12	2.49	15	3.12		CW		1-4-1		4-4	3-4-3	
					0.1	. ~	CCW		4-1-	-4	1-1	3-1-3	
RANCE IS ± DRAFT 1-1/2°	UNITS IN [mm]	[mm] SPEC. CONTRO									sta	ÇO	
	ALL DIMENSIONS APPLY AFTER PLATING						NSFORMER 0BCT-2				NER		
sed herein was originated by ( PRODUCTS CO., which reserves nufacturing, reproduction, use any article disclosed therein expressly granted to others. o vendor proprietary parts.		drawn by S.A. SMITH		DATE 9/25/97		FIRST	RST USED ON		D NOT LE DWG.	A Compon 301 Gaddi	ents Corporation of Ar s Boulevard Dayton, C	nerica Company hio 45403 USA	
		CHECKER			DATE W		APPROX.		E CODE	DWG. SIZE	DWG. NO.		
		ENGINEER	ENGINEER		DATE		SCALE 1-1		SHEET 1 OF 1		031–	3018	

## **Mouser Electronics**

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Staco: 1210BCT-2