

## STEVAL-TDR023V1

# RF power amplifier using 1 x PD55025-E N-channel enhancement-mode lateral MOSFETs

#### **Features**

Excellent thermal stabilityFrequency: 460 - 540 MHz

Supply voltage: 13.6 V
Output power: 20 W
Gain: 13.3 dB typ.
Efficiency: 51% - 66%

Load mismatch: 20:1BeO free amplifier

■ In compliance with the 2002/95/EC European directive

#### **Description**

The STEVAL-TDR023V1 is a common source N-channel enhancement-mode lateral field effect RF power amplifier designed for UHF mobile radio applications.




Table 1. Device summary

| iubic i. | Device Summary  |  |
|----------|-----------------|--|
|          | Part number     |  |
|          | STEVAL-TDR023V1 |  |
|          |                 |  |

Contents STEVAL-TDR023V1

#### **Contents**

| 1 | Electrical characteristics | 3 |
|---|----------------------------|---|
| 2 | Test circuit               | 4 |
| 3 | Circuit layout             | 5 |
| 4 | Revision history           | 7 |

## 1 Electrical characteristics

 $T_A = + 25$  °C,  $V_{DD} = 13.6$  V,  $I_{dq} = 150$  mA


Table 2. Electrical specification

| Symbol           | Test conditions                                   | Min. | Тур.    | Max. | Unit |
|------------------|---|------|---------|------|------|
| Freq             | Frequency range                                   | 460  |         | 540  | MHz  |
| P <sub>OUT</sub> |   |      | 20      |      | W    |
| Gain             | @ P <sub>OUT</sub> = 20W                          |      | 13.3    |      | dB   |
| Gain<br>flatness | @ P <sub>OUT</sub> = 20W                          |      |         | ±1.5 | dB   |
| Efficiency       | @ P <sub>OUT</sub> = 20W                          |      | 51 - 66 |      | %    |
| H2               | @ P <sub>OUT</sub> = 20W                          | -48  |         | -55  | dB   |
| НЗ               | @ P <sub>OUT</sub> = 20W                          | -55  |         | -60  | dB   |
| VSWR             | Load Mismatch all phases @ P <sub>OUT</sub> = 20W |      |         | 20:1 |      |

Test circuit STEVAL-TDR023V1

## 2 Test circuit

Figure 1. Test circuit schematic



STEVAL-TDR023V1 Circuit layout

# 3 Circuit layout

Figure 2. Circuit layout




Table 3. Component part list

|                  | Component part not |             |        |           |              |                      |
|------------------|--------------------|-------------|--------|-----------|--------------|----------------------|
| Part type        | Component ID       | Description | Value  | Case size | Manufacturer | Part code            |
| CAP              | C1                 | Capacitor   | 150pF  | 1206      | Murata       | GRM42-<br>6C0G151J50 |
| CAP              | C2                 | Capacitor   | 150pF  | 1206      | Murata       | GRM42-<br>6C0G151J50 |
| CAP              | СЗ                 | Capacitor   | 1 nF   | 1206      | Murata       | GRM42-<br>6C0G102J50 |
| CAP              | C4                 | Capacitor   | 10 nF  | 1206      | Murata       | GRM42-<br>6X7R104K50 |
| Electrolytic CAP | C5                 | Capacitor   | 220 μF |           |              |                      |
| Tantalum<br>CAP  | C6                 | Capacitor   | 1 μF   |           |              |                      |
| CAP              | C7                 | Capacitor   | 47pF   | 100B      | ATC          | 470                  |
| CAP              | C8                 | Capacitor   | 3.3pF  | 100B      | ATC          | 3R3                  |
| CAP              | C9                 | Capacitor   | 6.8pF  | 100B      | ATC          | 6R8                  |
| CAP              | C10                | Capacitor   | 39pF   | 100B      | ATC          | 390                  |
| CAP              | C11                | Capacitor   | 39pF   | 100B      | ATC          | 390                  |

Circuit layout STEVAL-TDR023V1

Table 3. Component part list (continued)

| Part type    | Component ID | Description          | Value                           | Case size                     | Manufacturer                       | Part code    |
|--------------|--------------|----------------------|---------------------------------|-------------------------------|------------------------------------|--------------|
| CAP          | C12          | Capacitor            | 5.6pF                           | 100B                          | ATC                                | 5R6          |
| CAP          | C13          | Capacitor            | 3.9pF                           | 100B                          | ATC                                | 3R9          |
| CAP          | C14          | Capacitor            | 47pF                            | 100B                          | ATC                                | 470          |
| TL           | TL1, TL7     | Transmission<br>Line | W = 2.87 mm L = 6 mm            |                               |                                    |              |
| TL           | TL2          | Transmission<br>Line |                                 | W                             | = 4.9 mm L = 5 mm                  |              |
| TL           | TL3, TL4     | Transmission<br>Line |                                 | W                             | / = 6 mm L = 3 mm                  |              |
| TL           | TL5          | Transmission<br>Line |                                 | W =                           | 4.9 mm L = 2.5 mm                  | 1            |
| TL           | TL6          | Transmission<br>Line | W = 4.9 mm L = 2.5 mm           |                               |                                    |              |
| Ferrite bead | B1           | Ferrite Bead         |                                 |                               | PANASONIC                          | EXCELDRC35C  |
| Ferrite bead | B2           | Ferrite Bead         |                                 |                               | PANASONIC                          | EXCELDRC35C  |
| INDUCTOR     | L1           | Inductor             | 43nH                            |                               | Coilcraft Mini<br>Spring           | B10TJ        |
| INDUCTOR     | L2           | Inductor             | 5nH Coilcraft Mini<br>Spring AC |                               | A02TJ                              |              |
| INDUCTOR     | L3           | Inductor             | 5nH                             | 5nH Coilcraft Mini Spring A02 |                                    | A02TJ        |
| Transistor   | PD55025-E    | LDMOS                |                                 |                               | STMicroelectronics PD550           |              |
| Resistor     | R1           | Resistor             | 15 ohms                         | 1206                          | TYCO ELECTRONICS 01623440-1        |              |
| POT          | R2           | Potentiometer        | 10 K                            |                               | BOURNS<br>ELECTRONICS 3214W-1-103E |              |
| Resistor     | R3           | Resistor             | 1K                              | 1206                          | TYCO<br>ELECTRONICS                | 01623440-1   |
| SMA-CONN     | RF in        | SMA-CONN             |                                 |                               | Johnson                            | 142-0701-801 |
| SMA-CONN     | RF out       | SMA-CONN             |                                 |                               | Johnson                            | 142-0701-801 |
| ZENER        | D1           | Zener Diode          | 5.1 V                           | SOD110                        | PHILIPS                            | BZX284C5V1   |
| Board        | FR-4 THk=    | :0.060" 2OZ Cu E     | Both Sides                      |                               |                                    |              |

STEVAL-TDR023V1 Revision history

# 4 Revision history

Table 4. Document revision history

| Date        | Revision | Changes          |
|-------------|----------|------------------|
| 11-Oct-2010 | 1        | Initial release. |

#### Please Read Carefully:

Information in this document is provided solely in connection with ST products. STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, modifications or improvements, to this document, and the products and services described herein at any time, without notice.

All ST products are sold pursuant to ST's terms and conditions of sale.

Purchasers are solely responsible for the choice, selection and use of the ST products and services described herein, and ST assumes no liability whatsoever relating to the choice, selection or use of the ST products and services described herein.

No license, express or implied, by estoppel or otherwise, to any intellectual property rights is granted under this document. If any part of this document refers to any third party products or services it shall not be deemed a license grant by ST for the use of such third party products or services, or any intellectual property contained therein or considered as a warranty covering the use in any manner whatsoever of such third party products or services or any intellectual property contained therein.

UNLESS OTHERWISE SET FORTH IN ST'S TERMS AND CONDITIONS OF SALE ST DISCLAIMS ANY EXPRESS OR IMPLIED WARRANTY WITH RESPECT TO THE USE AND/OR SALE OF ST PRODUCTS INCLUDING WITHOUT LIMITATION IMPLIED WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE (AND THEIR EQUIVALENTS UNDER THE LAWS OF ANY JURISDICTION), OR INFRINGEMENT OF ANY PATENT, COPYRIGHT OR OTHER INTELLECTUAL PROPERTY RIGHT.

UNLESS EXPRESSLY APPROVED IN WRITING BY AN AUTHORIZED ST REPRESENTATIVE, ST PRODUCTS ARE NOT RECOMMENDED, AUTHORIZED OR WARRANTED FOR USE IN MILITARY, AIR CRAFT, SPACE, LIFE SAVING, OR LIFE SUSTAINING APPLICATIONS, NOR IN PRODUCTS OR SYSTEMS WHERE FAILURE OR MALFUNCTION MAY RESULT IN PERSONAL INJURY, DEATH, OR SEVERE PROPERTY OR ENVIRONMENTAL DAMAGE. ST PRODUCTS WHICH ARE NOT SPECIFIED AS "AUTOMOTIVE GRADE" MAY ONLY BE USED IN AUTOMOTIVE APPLICATIONS AT USER'S OWN RISK.

Resale of ST products with provisions different from the statements and/or technical features set forth in this document shall immediately void any warranty granted by ST for the ST product or service described herein and shall not create or extend in any manner whatsoever, any liability of ST.

ST and the ST logo are trademarks or registered trademarks of ST in various countries.

Information in this document supersedes and replaces all information previously supplied.

The ST logo is a registered trademark of STMicroelectronics. All other names are the property of their respective owners.

© 2010 STMicroelectronics - All rights reserved

STMicroelectronics group of companies

Australia - Belgium - Brazil - Canada - China - Czech Republic - Finland - France - Germany - Hong Kong - India - Israel - Italy - Japan - Malaysia - Malta - Morocco - Philippines - Singapore - Spain - Sweden - Switzerland - United Kingdom - United States of America

www.st.com

**577** 

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

STMicroelectronics: STEVAL-TDR023V1