



Automotive-grade silicon carbide Power MOSFET 1200 V, 12 A, 520 mΩ (typ., $T_J = 150\text{ }^{\circ}\text{C}$) in an HiP247™ package



HiP247™



Features

- AEC-Q101 qualified 
- Very tight variation of on-resistance vs. temperature
- Very high operating temperature capability ($T_J = 200\text{ }^{\circ}\text{C}$)
- Very fast and robust intrinsic body diode
- Low capacitance

Applications

- Motor drives
- EV chargers
- High voltage DC-DC converters
- Switch mode power supplies

Description

This silicon carbide Power MOSFET is produced exploiting the advanced, innovative properties of wide bandgap materials. This results in unsurpassed on-resistance per unit area and very good switching performance almost independent of temperature. The outstanding thermal properties of the SiC material, combined with the device's housing in the proprietary HiP247™ package, allows designers to use an industry-standard outline with significantly improved thermal capability. These features render the device perfectly suitable for high-efficiency and high power density applications.

Product status link

[SCT10N120AG](#)

Product summary

Order code	SCT10N120AG
Marking	SCT10N120AG
Package	HiP247™
Packing	Tube

1 Electrical ratings

Table 1. Absolute maximum ratings

Symbol	Parameter	Value	Unit
V_{DS}	Drain-source voltage	1200	V
V_{GS}	Gate-source voltage	-10 to 25	V
I_D	Drain current (continuous) at $T_C = 25\text{ °C}$	12	A
I_D	Drain current (continuous) at $T_C = 100\text{ °C}$	10	A
$I_{DM}^{(1)}$	Drain current (pulsed)	24	A
P_{TOT}	Total power dissipation at $T_C = 25\text{ °C}$	150	W
T_{stg}	Storage temperature range	-55 to 200	°C
T_j	Operating junction temperature range		°C

1. Pulse width limited by safe operating area.

Table 2. Thermal data

Symbol	Parameter	Value	Unit
$R_{thj-case}$	Thermal resistance junction-case	1.17	°C/W
$R_{thj-amb}$	Thermal resistance junction-ambient	40	°C/W

2 Electrical characteristics

(T_{CASE} = 25 °C unless otherwise specified).

Table 3. On/off states

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
V _{(BR)DSS}	Drain-source breakdown voltage	V _{GS} = 0 V, I _D = 1 mA	1200			V
I _{DSS}	Zero gate voltage drain current	V _{DS} = 1200 V, V _{GS} = 0 V			10	μA
		V _{DS} = 1200 V, V _{GS} = 0 V, T _J = 200 °C ⁽¹⁾			100	μA
I _{GSS}	Gate-body leakage current	V _{DS} = 0 V, V _{GS} = -10 to 25 V			100	nA
V _{GS(th)}	Gate threshold voltage	V _{DS} = V _{GS} , I _D = 250 μA	1.8	3.5		V
R _{DS(on)}	Static drain-source on-resistance	V _{GS} = 20 V, I _D = 6 A		500	690	mΩ
		V _{GS} = 20 V, I _D = 6 A, T _J = 150 °C		520		mΩ
		V _{GS} = 20 V, I _D = 6 A, T _J = 200 °C		580		mΩ

1. Defined by design, not subject to production test.

Table 4. Dynamic

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
C _{iss}	Input capacitance	V _{DS} = 400 V, f = 1 MHz, V _{GS} = 0 V	-	290	-	pF
C _{oss}	Output capacitance		-	30	-	pF
C _{rss}	Reverse transfer capacitance		-	9	-	pF
Q _g	Total gate charge	V _{DD} = 800 V, I _D = 6 A, V _{GS} = 0 to 20 V	-	22	-	nC
Q _{gs}	Gate-source charge		-	3	-	nC
Q _{gd}	Gate-drain charge		-	10	-	nC
R _g	Gate input resistance	f=1 MHz, I _D =0 A	-	8	-	Ω

Table 5. Switching energy (inductive load)

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
E _{on}	Turn-on switching energy	V _{DD} = 800 V, I _D = 6 A R _G = 10 Ω, V _{GS} = -5 to 20 V	-	90	-	μJ
E _{off}	Turn-off switching energy		-	30	-	μJ
E _{on}	Turn-on switching energy	V _{DD} = 800 V, I _D = 6 A R _G = 10 Ω, V _{GS} = -5 to 20 V T _J = 150 °C	-	104	-	μJ
E _{off}	Turn-off switching energy		-	33	-	μJ

Table 6. Switching times

Symbol	Parameter	Test conditions	Min.	Typ.	Max.	Unit
$t_{d(on)}$	Turn-on delay time	$V_{DD} = 800\text{ V}$, $I_D = 6\text{ A}$, $R_G = 10\ \Omega$, $V_{GS} = -5\text{ to }20\text{ V}$	-	7	-	ns
t_f	Fall time		-	17	-	ns
$t_{d(off)}$	Turn-off delay time		-	14	-	ns
t_r	Rise time		-	12	-	ns

Table 7. Reverse SiC diode characteristics

Symbol	Parameter	Test conditions	Min	Typ.	Max	Unit
V_{SD}	Diode forward voltage	$I_F = 6\text{ A}$, $V_{GS} = 0\text{ V}$	-	4.3	-	V
t_{rr}	Reverse recovery time	$I_{SD} = 6\text{ A}$, $di/dt = 2000\text{ A}/\mu\text{s}$ $V_{DD} = 800\text{ V}$, $T_J = 150\text{ }^\circ\text{C}$	-	16	-	ns
Q_{rr}	Reverse recovery charge		-	107	-	nC
I_{RRM}	Reverse recovery current		-	12	-	A

2.1 Electrical characteristics (curves)

Figure 1. Safe operating area




Figure 2. Thermal impedance




Figure 3. Output characteristics (T_J = 25 °C)




Figure 4. Output characteristics (T_J = 150 °C)




Figure 5. Output characteristics ($T_J = 200^\circ\text{C}$)




Figure 6. Transfer characteristics




Figure 7. Power dissipation




Figure 8. Gate charge vs gate-source voltage




Figure 9. Capacitance variations




Figure 10. Switching energy vs. drain current




Figure 11. Switching energy vs. junction temperature




Figure 12. Normalized $V_{(\text{BR})\text{DSS}}$ vs. temperature




Figure 13. Normalized gate threshold voltage vs. temperature




Figure 14. Normalized on-resistance vs. temperature




Figure 15. Body diode characteristics ($T_J = -50^{\circ}\text{C}$)




Figure 16. Body diode characteristics ($T_J = 25^{\circ}\text{C}$)




Figure 17. Body diode characteristics ($T_J = 150\text{ }^{\circ}\text{C}$)




Figure 18. 3rd quadrant characteristics ($T_J = -50\text{ }^{\circ}\text{C}$)




Figure 19. 3rd quadrant characteristics ($T_J = 25\text{ }^{\circ}\text{C}$)







Figure 20. 3rd quadrant characteristics ($T_J = 150\text{ }^{\circ}\text{C}$)



3 Test circuits

Figure 21. Switching test waveforms for transition times


GIPD101020141511FSR

Figure 22. Clamped inductive switching waveform



GIPD101020141502FSR

4 Package information

In order to meet environmental requirements, ST offers these devices in different grades of **ECOPACK®** packages, depending on their level of environmental compliance. ECOPACK® specifications, grade definitions and product status are available at: www.st.com. ECOPACK® is an ST trademark.

4.1 HiP247 package information

Figure 23. HiP247™ package outline



8581091_2

Table 8. HiP247™ package mechanical data

Dim.	mm		
	Min.	Typ.	Max.
A	4.85	5.00	5.15
A1	2.20		2.60
A2	1.90	2.00	2.10
b	1.00		1.40
b1	2.00		2.40
b2	3.00		3.40
c	0.40		0.80
D	19.85	20.00	20.15
E	15.45	15.60	15.75
E3	1.45		1.65
e	5.30	5.45	5.60
L	14.20		14.80
L1	3.70		4.30
L2	18.30	18.50	18.70
P	3.55		3.65
Q	5.65		5.95
S	5.30	5.50	5.70

Revision history

Table 9. Document revision history

Date	Revision	Changes
20-Mar-2018	1	First release
01-Mar-2019	2	Updated Table 3. On/off states . Updated package information.

Contents

1	Electrical ratings	2
2	Electrical characteristics.....	3
2.1	Electrical characteristics (curves)	5
3	Test circuits	9
4	Package information.....	10
4.1	HiP247 package information	10
	Revision history	12

IMPORTANT NOTICE – PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2019 STMicroelectronics – All rights reserved

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[STMicroelectronics:](#)

[SCT10N120AG](#)