



## Automotive 600 W TVS in SOD128 Flat



### Features

- AEC-Q101 qualified 
- Peak pulse power: 600 W (10/1000  $\mu$ s) and 4 kW (8/20  $\mu$ s)
- Stand-off voltage range from 5 V to 36 V
- Unidirectional type
- Low leakage current: 0.2  $\mu$ A at 25 °C and 1  $\mu$ A at 85 °C
- Operating  $T_j$  max: 175 °C
- High power capability at 175 °C ( $T_j$  max.) up to 240 W (10/1000  $\mu$ s)
- Lead finishing: matte tin plating

### Complies with the following standards

- UL94, V0
- J-STD-020 MSL level 1
- J-STD-002, JESD 22-B102 E3 and MIL-STD-750, method 2026 solderable matte tin plated leads
- JESD-201 class 2 whisker test
- IPC7531 footprint
- JEDEC registered package outline
- IEC 61000-4-4 level 4:
  - 4 kV
- ISO10605, IEC 61000-4-2, C= 150 pF - R = 330  $\Omega$  exceeds level 4:
  - 30 kV (air discharge)
  - 30 kV (contact discharge)
- ISO10605 - C = 330 pF, R = 330  $\Omega$  exceeds level 4:
  - 30 kV (air discharge)
  - 30 kV (contact discharge)
- ISO7637-2 (Not applicable to parts with stand-off voltage lower than battery voltage)
  - Pulse1:  $V_S = -150$  V
  - Pulse 2a:  $V_S = +112$  V
  - Pulse 3a:  $V_S = -220$  V
  - Pulse 3b:  $V_S = +150$  V

### Description

The SM6FY series are designed to protect sensitive automotive circuits against surges defined in ISO 7637-2 and against electrostatic discharges according to ISO 10605.

The Planar technology makes it compatible with high-end circuits where low leakage current and high junction temperature are required to provide long term reliability and stability.

| Product status link |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                   |
|---------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| SM6FY               | <a href="#">SM6F5.0AY</a> , <a href="#">SM6F6.0AY</a> ,<br><a href="#">SM6F6.5AY</a> , <a href="#">SM6F8.5AY</a> ,<br><a href="#">SM6F10AY</a> , <a href="#">SM6F11AY</a> ,<br><a href="#">SM6F13AY</a> , <a href="#">SM6F12AY</a> ,<br><a href="#">SM6F14AY</a> , <a href="#">SM6F15AY</a> ,<br><a href="#">SM6F16AY</a> , <a href="#">SM6F18AY</a> ,<br><a href="#">SM6F20AY</a> , <a href="#">SM6F22AY</a> ,<br><a href="#">SM6F23AY</a> , <a href="#">SM6F24AY</a> ,<br><a href="#">SM6F26AY</a> , <a href="#">SM6F28AY</a> ,<br><a href="#">SM6F30AY</a> , <a href="#">SM6F31AY</a> ,<br><a href="#">SM6F33AY</a> , <a href="#">SM6F36AY</a> |



# 1 Characteristics

**Table 1. Absolute maximum ratings ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ )**

| Symbol    | Parameter                                          |                                                          | Value       | Unit               |
|-----------|----------------------------------------------------|----------------------------------------------------------|-------------|--------------------|
| $V_{PP}$  | Peak pulse voltage                                 | ISO10605 (C = 330 pF, R = 330 $\Omega$ ):                |             |                    |
|           |                                                    | Contact discharge                                        | 30          | kV                 |
|           |                                                    | Air discharge                                            | 30          |                    |
|           |                                                    | ISO10605 / IEC 61000-4-2 (C = 150 pF, R = 330 $\Omega$ ) |             |                    |
|           |                                                    | Contact discharge                                        | 30          |                    |
|           |                                                    | Air discharge                                            | 30          |                    |
| $P_{PP}$  | Peak pulse power dissipation                       | 10/1000 $\mu\text{s}$ , $T_j$ initial = $T_{amb}$        | 600         | W                  |
| $T_{stg}$ | Storage temperature range                          |                                                          | -65 to +175 | $^{\circ}\text{C}$ |
| $T_j$     | Operating junction temperature range               |                                                          | -55 to +175 | $^{\circ}\text{C}$ |
| $T_L$     | Maximum lead temperature for soldering during 10 s |                                                          | 260         | $^{\circ}\text{C}$ |

**Figure 1. Electrical characteristics - parameter definitions**

|            |                                    |
|------------|------------------------------------|
| $V_{RM}$   | Maximum stand - off voltage        |
| $I_{RM}$   | Maximum leakage current @ $V_{RM}$ |
| $V_{BR}$   | Breakdown voltage @ $I_{BR}$       |
| $I_{BR}$   | Breakdown current                  |
| $V_{CL}$   | Clamping voltage @ $I_{PP}$        |
| $I_{PP}$   | Peak pulse current                 |
| $R_D$      | Dynamic resistance                 |
| $V_F$      | Forward voltage drop @ $I_F$       |
| $I_F$      | Forward current                    |
| $\alpha T$ | Voltage temperature coefficient    |


**Figure 2. Pulse definition for electrical characteristics**



**Table 2. Electrical characteristics - parameter values ( $T_{amb} = 25\text{ }^{\circ}\text{C}$ , unless otherwise specified)**

| Type      | $I_{RM}$ max at $V_{RM}$ |                       |     | $V_{BR}$ at $I_{BR}^{(1)}$ |      |      |    | 10 / 1000 $\mu\text{s}$ |                |          | 8 / 20 $\mu\text{s}$ |                |          | $\alpha T$                 |
|-----------|--------------------------|-----------------------|-----|----------------------------|------|------|----|-------------------------|----------------|----------|----------------------|----------------|----------|----------------------------|
|           |                          |                       |     |                            |      |      |    | $V_{CL}^{(2)(3)}$       | $I_{PP}^{(4)}$ | $R_D$    | $V_{CL}^{(2)(3)}$    | $I_{PP}^{(4)}$ | $R_D$    |                            |
|           | 25 $^{\circ}\text{C}$    | 85 $^{\circ}\text{C}$ |     | Min.                       | Typ. | Max. |    | Max.                    |                | Max.     | Max.                 |                | Max.     | Max.                       |
|           | $\mu\text{A}$            |                       | V   | V                          |      |      | mA | V                       | A              | $\Omega$ | V                    | A              | $\Omega$ | $10^{-4}/^{\circ}\text{C}$ |
| SM6F5.0AY | 20                       | 50                    | 5.0 | 6.4                        | 6.74 | 7.1  | 10 | 9.2                     | 68             | 0.031    | 13.4                 | 298            | 0.021    | 5.7                        |
| SM6F6.0AY | 20                       | 50                    | 6.0 | 6.7                        | 7.05 | 7.4  | 10 | 10.3                    | 61             | 0.048    | 13.7                 | 290            | 0.022    | 5.9                        |
| SM6F6.5AY | 20                       | 50                    | 6.5 | 7.2                        | 7.58 | 8    | 10 | 11.2                    | 56             | 0.057    | 14.5                 | 276            | 0.024    | 6.1                        |
| SM6F8.5AY | 20                       | 50                    | 8.5 | 9.4                        | 9.9  | 10.4 | 1  | 14.4                    | 41.7           | 0.096    | 19.5                 | 205            | 0.044    | 7.3                        |
| SM6F10AY  | 0.2                      | 1                     | 10  | 11.1                       | 11.7 | 12.3 | 1  | 17                      | 37             | 0.127    | 21.7                 | 184            | 0.051    | 7.8                        |
| SM6F11AY  | 0.2                      | 1                     | 11  | 12.3                       | 13   | 13.7 | 1  | 18                      | 33.8           | 0.127    | 24.2                 | 1665           | 0.064    | 8.1                        |
| SM6F12AY  | 0.2                      | 1                     | 12  | 13.3                       | 14   | 14.7 | 1  | 19.9                    | 31             | 0.168    | 25.3                 | 157            | 0.068    | 8.3                        |
| SM6F13AY  | 0.2                      | 1                     | 13  | 14.4                       | 15.2 | 16   | 1  | 21.5                    | 29             | 0.190    | 27.2                 | 147            | 0.076    | 8.4                        |
| SM6F14AY  | 0.2                      | 1                     | 14  | 15.7                       | 16.5 | 17.3 | 1  | 23.1                    | 26             | 0.223    | 29                   | 136            | 0.086    | 8.6                        |
| SM6F15AY  | 0.2                      | 1                     | 15  | 16.7                       | 17.6 | 18.5 | 1  | 24.4                    | 25.1           | 0.235    | 32.5                 | 123            | 0.114    | 8.8                        |
| SM6F16AY  | 0.2                      | 1                     | 16  | 17.9                       | 18.8 | 19.8 | 1  | 26                      | 23.1           | 0.268    | 34.7                 | 115            | 0.130    | 9.0                        |
| SM6F18AY  | 0.2                      | 1                     | 18  | 20                         | 21.1 | 22.2 | 1  | 29.2                    | 21.5           | 0.326    | 39.3                 | 102            | 0.168    | 9.2                        |
| SM6F20AY  | 0.2                      | 1                     | 20  | 22.2                       | 23.4 | 24.6 | 1  | 32.4                    | 19.4           | 0.402    | 42.8                 | 93             | 0.196    | 9.4                        |
| SM6F22AY  | 0.2                      | 1                     | 22  | 24.4                       | 25.7 | 27   | 1  | 35.5                    | 17.7           | 0.480    | 48.3                 | 83             | 0.257    | 9.6                        |
| SM6F23AY  | 0.2                      | 1                     | 23  | 25.7                       | 27   | 28.4 | 1  | 37.8                    | 16.4           | 0.573    | 49.2                 | 81             | 0.257    | 9.6                        |
| SM6F24AY  | 0.2                      | 1                     | 24  | 26.7                       | 28.1 | 29.5 | 1  | 38.9                    | 16             | 0.588    | 50                   | 80             | 0.256    | 9.6                        |
| SM6F26AY  | 0.2                      | 1                     | 26  | 28.9                       | 30.4 | 31.9 | 1  | 42.1                    | 14.9           | 0.685    | 53.5                 | 75             | 0.288    | 9.7                        |
| SM6F28AY  | 0.2                      | 1                     | 28  | 31.1                       | 32.7 | 34.3 | 1  | 45.4                    | 13.8           | 0.804    | 59                   | 68             | 0.363    | 9.8                        |
| SM6F30AY  | 0.2                      | 1                     | 30  | 33.2                       | 35   | 36.8 | 1  | 48.4                    | 13             | 0.885    | 64.3                 | 62             | 0.442    | 9.9                        |
| SM6F31AY  | 0.2                      | 1                     | 31  | 34.2                       | 36   | 37.8 | 1  | 50.2                    | 12.3           | 1.01     | 65                   | 61             | 0.45     | 9.9                        |
| SM6F33AY  | 0.2                      | 1                     | 33  | 36.7                       | 38.6 | 40.5 | 1  | 53.3                    | 11.8           | 1.08     | 69.7                 | 57             | 0.512    | 10                         |
| SM6F36AY  | 0.2                      | 1                     | 36  | 40                         | 42.1 | 44.2 | 1  | 58.1                    | 10.3           | 1.35     | 76                   | 52             | 0.612    | 10                         |


1. To calculate  $V_{BR}$  versus  $T_j$ :  $V_{BR}$  at  $T_j = V_{BR}$  at  $25\text{ }^{\circ}\text{C} \times (1 + \alpha T \times (T_j - 25))$
2. To calculate  $V_{CL}$  versus  $T_j$ :  $V_{CL}$  at  $T_j = V_{CL}$  at  $25\text{ }^{\circ}\text{C} \times (1 + \alpha T \times (T_j - 25))$
3. To calculate  $V_{CL}$  max versus  $I_{PPappli}$ :  $V_{CLmax} = V_{BRmax} + R_D \times I_{PPappli}$
4. Surge capability given for both directions

## 1.1 Characteristics (curves)


**Figure 3. Maximum peak power dissipation versus initial junction temperature**




**Figure 4. Maximum peak pulse power versus exponential pulse duration**




**Figure 5. Maximum peak pulse current versus clamping voltage**




**Figure 6. Dynamic resistance versus pulse duration**




**Figure 7. Junction capacitance versus reverse applied voltage (unidirectional types)**




**Figure 8. Leakage current versus junction temperature**




**Figure 9. Peak forward voltage drop versus peak forward current**




**Figure 10. Thermal impedance junction to ambient versus pulse duration**




**Figure 11. Thermal resistance junction to ambient versus copper area under each lead (SOD128 Flat)**




**Figure 12. ISO7637-2 pulse 1: V\_s = -150 V with 12 V battery**




**Figure 13.** ISO7637-2 pulse 2a:  $V_s = +112\text{ V}$  with 12 V battery



**Figure 14.** ISO7637-2 pulse 3a:  $V_s = -220\text{ V}$  with 12 V battery



**Figure 15.** ISO7637-2 pulse 3b:  $V_s = +150\text{ V}$  with 12 V battery




## 2 Package information

In order to meet environmental requirements, ST offers these devices in different grades of **ECOPACK** packages, depending on their level of environmental compliance. ECOPACK specifications, grade definitions and product status are available at: [www.st.com](http://www.st.com). ECOPACK is an ST trademark.

### 2.1 SOD128 Flat package information

**Figure 16. SOD128 Flat package outline**




**Table 3. SOD128 Flat package mechanical data**

| Ref. | Dimensions  |      |                       |       |
|------|-------------|------|-----------------------|-------|
|      | Millimeters |      | Inches <sup>(1)</sup> |       |
|      | Min.        | Max. | Min.                  | Max.  |
| A    | 0.93        | 1.03 | 0.037                 | 0.041 |
| b    | 1.69        | 1.81 | 0.067                 | 0.071 |
| c    | 0.10        | 0.22 | 0.004                 | 0.009 |
| D    | 2.30        | 2.50 | 0.091                 | 0.098 |
| E    | 4.60        | 4.80 | 0.181                 | 0.189 |
| E1   | 3.70        | 3.90 | 0.146                 | 0.154 |
| L    | 0.55        | 0.85 | 0.026                 | 0.033 |
| L1   | 0.30 typ.   |      | 0.012 typ.            |       |
| L2   | 0.45 typ.   |      | 0.018 typ.            |       |


1. Values in inches are converted from mm and rounded to 3 decimal digits

## 2.2 SOD128 Flat packing info


**Figure 17. Footprint recommendations, dimensions in mm (inches)**



**Figure 18. Marking layout (refer to ordering information table for marking)**




**Figure 19. Package orientation in reel**




Taped according to EIA-481

Note: Pocket dimensions are not on scale  
Pocket shape may vary depending on package  
On bidirectional devices, marking and logo may be not always in the same direction


**Figure 20. Tape and reel orientation**




**Figure 21. Reel dimensions (mm)**



**Figure 22. Inner box dimensions (mm)**




**Figure 23. Tape and reel outline**


Note: Pocket dimensions are not on scale  
Pocket shape may vary depending on package

**Table 4. Tape and reel mechanical data**

| Ref.             | Dimensions  |       |       |
|------------------|-------------|-------|-------|
|                  | Millimeters |       |       |
|                  | Min.        | Typ.  | Max.  |
| $\varnothing D0$ | 1.5         | 1.55  | 1.60  |
| $\varnothing D1$ | 1.5         |       |       |
| F                | 5.45        | 5.50  | 5.55  |
| K0               | 1.20        | 1.25  | 1.30  |
| P0               | 3.90        | 4.00  | 4.10  |
| P1               | 3.90        | 4.00  | 4.10  |
| P2               | 1.90        | 2.00  | 2.10  |
| W                | 11.70       | 12.00 | 12.30 |

**Figure 24. ST ECOPACK® recommended soldering reflow profile for PCB mounting**



**Note:** Minimize air convection currents in the reflow oven to avoid component movement. Maximum soldering profile corresponds to the latest IPC/JEDEC J-STD-020.

### **3 Application and design guidelines**

---

More information is available in the application note AN2689 "Protection of automotive electronics from electrical hazards, guidelines for design and component selection".

## 4 Ordering information

Figure 25. Ordering information scheme




Table 5. Ordering information

| Order code | Marking                               | Package     | Weight | Base qty. | Delivery mode |
|------------|---------------------------------------|-------------|--------|-----------|---------------|
| SM6FxxAY   | See <a href="#">Table 6. Marking.</a> | SOD128 Flat | 28 mg  | 3000      | Tape and reel |

**Table 6. Marking**

| Order code | Marking |
|------------|---------|
| SM6F5.0AY  | 5AIY    |
| SM6F6.0AY  | 5AKY    |
| SM6F6.5AY  | 5ALY    |
| SM6F8.5AY  | 5APY    |
| SM6F10AY   | 5ASY    |
| SM6F11AY   | 5AUY    |
| SM6F12AY   | 5AWY    |
| SM6F13AY   | 5AYY    |
| SM6F14AY   | 5BAY    |
| SM6F15AY   | 5BCY    |
| SM6F16AY   | 5BEY    |
| SM6F18AY   | 5BIY    |
| SM6F20AY   | 5BMY    |
| SM6F22AY   | 5BOY    |
| SM6F23AY   | 5BPY    |
| SM6F24AY   | 5BQY    |
| SM6F26AY   | 5BSY    |
| SM6F28AY   | 5BUY    |
| SM6F30AY   | 5BWY    |
| SM6F31AY   | 5BXY    |
| SM6F33AY   | 5BZY    |
| SM6F36AY   | 5CCY    |

## Revision history

**Table 7. Document revision history**

| Date        | Revision | Changes               |
|-------------|----------|-----------------------|
| 01-Jul-2019 | 1        | Initial release.      |
| 07-Jan-2020 | 2        | Updated links syntax. |

**IMPORTANT NOTICE – PLEASE READ CAREFULLY**

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, please refer to [www.st.com/trademarks](http://www.st.com/trademarks). All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2020 STMicroelectronics – All rights reserved

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

## STMicroelectronics:

[SM6F26AY](#) [SM6F16AY](#) [SM6F6.5AY](#) [SM6F13AY](#) [SM6F22AY](#) [SM6F24AY](#) [SM6F20AY](#) [SM6F15AY](#) [SM6F10AY](#)  
[SM6F30AY](#) [SM6F36AY](#) [SM6F28AY](#) [SM6F5.0AY](#) [SM6F33AY](#) [SM6F23AY](#) [SM6F31AY](#) [SM6F6.0AY](#) [SM6F14AY](#)  
[SM6F8.5AY](#) [SM6F11AY](#) [SM6F12AY](#) [SM6F18AY](#)