

Voice user interface evaluation kit



Features

- STM32H753VIT6E high-performance MCU with 2 MB embedded Flash, 1 Mb embedded SRAM and in cost-effective LQFP package
- 2.4 GHz Wi-Fi subsystem with Murata 1DX module used in bypass mode coupled to ISSI IS25LP016D 2 MBytes NOR Flash memory
- 3 x MP23DB01HP MEMS microphones with 36 and 30 mm spacing
- FDA903D class D digital input automotive audio amplifier
- 8 Ohm loudspeaker
- 4 RGB LEDs and 4 simple LEDs
- · Joystick, reset and user push buttons
- · High modularity with mother/daughter board
- Small 36x65 mm² footprint with simple and cost-effective PCB design

Description

The STEVAL-VOICE-UI Amazon™ qualified evaluation kit is designed to allow evaluation of a cost-effective way to integrate AVS for AWS IoT Services® into smart devices, so they can implement state-of-art, hands-free voice control based on natural language comprehension.

Users will therefore enjoy a heightened experience with target IoT end products, with the ability to talk to Amazon Alexa® and control smart home devices, get assistance, listen to the news, check the weather forecast, play music, etc.

The software package implements audio front-end, Amazon wake word, audio playback and Amazon Alexa communication protocol software. The SDK runs on internal memories only, offering maximum integration and cost-effective solutions.

The STEVAL-VOICE-UI is built with a modular approach for easy prototyping and debugging purposes as well as easy adaptation to specific microphone spacings, user interface and audio output requirements.

Product summary		
Voice user interface evaluation kit	STEVAL-VOICE-UI	
High-performance ARM Cortex-M7 MCU with DP- FPU	STM32H753VIT6E	
MEMS Multi performance mode digital microphone with same sensitivity value for each operative mode	MP23DB01HP	
1 x 45 W class D digital input automotive power amplifier	FDA903D	
Applications	IoT for Smart Home and City	
	IoT for Smart Things	



1 Block diagram

Voice Input

Digital Microphone

Digital Microphone

Audio Output

Audio Output

Audio Amplifier

Audio Amplifier

Figure 1. STEVAL-VOICE-UI functional block diagram

DB4346 - Rev 1 page 2/4



Revision history

Table 1. Document revision history

Date	Version	Changes
09-Nov-2020	1	Initial release.

DB4346 - Rev 1 page 3/4



IMPORTANT NOTICE - PLEASE READ CAREFULLY

STMicroelectronics NV and its subsidiaries ("ST") reserve the right to make changes, corrections, enhancements, modifications, and improvements to ST products and/or to this document at any time without notice. Purchasers should obtain the latest relevant information on ST products before placing orders. ST products are sold pursuant to ST's terms and conditions of sale in place at the time of order acknowledgement.

Purchasers are solely responsible for the choice, selection, and use of ST products and ST assumes no liability for application assistance or the design of Purchasers' products.

No license, express or implied, to any intellectual property right is granted by ST herein.

Resale of ST products with provisions different from the information set forth herein shall void any warranty granted by ST for such product.

ST and the ST logo are trademarks of ST. For additional information about ST trademarks, please refer to www.st.com/trademarks. All other product or service names are the property of their respective owners.

Information in this document supersedes and replaces information previously supplied in any prior versions of this document.

© 2020 STMicroelectronics - All rights reserved

DB4346 - Rev 1 page 4/4

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

STMicroelectronics: