

DB25F AND TRS WIRING CHART									
TRS	CABLE	TIP	RING	SLEEVE					
(CHANNEL)	(COLOR)	(RED)	(BLACK)	(BARE)					
1	BROWN	24	12	25					
2	RED	10	23	11					
3	ORANGE	21	9	22					
4	YELLOW	7	20	8					
5	GREEN	18	6	19					
6	BLUE	4	17	5					
7	PURPLE	15	3	16					

14

(CUSTOMER DRAWING)

GRAY

CHANNEL 3

CHANNEL 4

**DB25F PIN-OUT VIEW** 

## NOTES:

- 1. BREAKOUT CABLE LENGTH: 18 +/- 0.75 INCHES. SEE TABLE FOR COLOR.
- $\langle$  B $\rangle$  2. THIS PRODUCT COMES COILED AND PACKAGED IN BAG.

B 3. MATERIALS:
TRS PLUG AND HANDLE - COPPER ALLOY, NICKEL PLATED
THE PMOPI ASTIC DSUB:

CABLE CLAMP - COPPER, NICKEL PLATED SHELL - STEEL, TIN PLATED

**INSULATORS - THERMOPLASTIC** 

SCREW LOCKS - COPPER ALLOY, NICKEL PLATED

4. THIS PRODUCT IS RoHS COMPLIANT.

		THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED  BY SWITCHCRAFT INC. AND IS DELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION DURPOSES ONLY

						THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.							
					UNLESS OTHERWISE SPECIFIED	SIZE	W	/IDTH	MULT		LBS/M	TEMP	ER
					1. ALL DIMENSIONS IN INCHES [mm]	FINISH				MATERIAL			
					- TWO PLACE DECIMALS ±0.02 [0.5]	SPEC No.				SPEC No.			
						FIRST USED ON SCALE 1:2						•	
С	27520	06/08/15	PC	TJK	- THREE PLACE DECIMALS ±0.005 [0.13]					Swilehera fi"			
В	26637	10/4/10	RS	TJK		DATE DRAWN	The state of the s		APVD				
						7/16/09	JGK	RS	TJK				
Α	26568	7/20/10	RS	TJK		7/10/09	JGK	12/1/10	12/1/10		SHEET 1	OF	1
REV	ECO NUMBER	DATE	BY	APVD		NAME				PART No		_	REV
REVISIONS				DO NOT SCALE DRAWING	DB25F TO 8-TRS, RoHS			DB25FTRS C					

SolidWorks CAD File B

## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Switchcraft:

DB25FTRS