

(13/12)(1) (19/9)(8) (7)(6)(5) (4)(3)(2) (25 (2) (2) (2) (2) (9) (18 (7) (6) (5) (25 (2) (2) (2) (2) (9) (18 (7) (6) (5)

CHANNEL

DB25F PIN-OUT VIEW

9

	DB25F AND XLRM WIRING CHART									
XLR	XLR	CABLE	PIN 2	PIN 3	PIN 1					
(CHANNEL)	(DESC.)	(COLOR)	(RED)	(BLACK)	(BARE)					
1	XLRM	BROWN	24	12	25					
2	XLRM	RED	10	23	11					
3	XLRM	ORANGE	21	9	22					
4	XLRM	YELLOW	7	20	8					
5	XLRM	GREEN	18	6	19					
6	XLRM	BLUE	4	17	5					
7	XLRM	PURPLE	15	3	16					
8	XLRM	GRAY	1	14	2					

(CUSTOMER DRAWING)

NOTES:

- 1. BREAKOUT CABLE LENGTH: 18 +/- 0.75 INCHES. SEE TABLE FOR COLOR.
- (B) 2. THIS PRODUCT COMES COILED AND PACKAGED IN BAG.
- B 3. MATERIALS:
 XLR CONNECTORS:
 HANDLE ZINC ALLOY, NICKEL PLATED
 HOUSING AND LATCH ZINC ALLOY, NICKEL PLATED
 INSULATOR THERMOPLASTIC, GREEN
 PINS SPECIAL COPPER ALLOY, SILVER PLATED
 H.S. TUBING THERMOPLASTIC
 DSUB:
 CABLE CLAMP COPPER, NICKEL PLATED
 SHELL STEEL, TIN PLATED
 INSULATORS THERMOPLASTIC
 SCREW LOCKS BRASS, NICKEL PLATED

4. THIS PRODUCT IS RoHS COMPLIANT.

							THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.								
						UNLESS OTHERWISE SPECIFIED	SIZE	W	/IDTH MULT			LBS/M		TEMPER	R
						1. ALL DIMENSIONS IN INCHES [mm]	FINISH			•	MATERIAL				
						- TWO PLACE DECIMALS ±0.02 [0.5]				SPEC No.					
	С	27520	06/08/15	PC	TJK	- THREE PLACE DECIMALS ±0.005 [0.13]			N	SCALE 1:2	-Switcheraft*				
	В	26637	10/4/10	RS	TJK										
		20500	7/00/40		T 11/		7/16/09	JGK	RS	TJK					
	Α	26568	7/20/10	RS	TJK		17.10700		11/30/10	11/30/10		SHEET	1	of 1	
	REV	ECO NUMBER	DATE	BY	APVD		NAME	1	1		PART No	=		_	REV
REVISIONS			•	DO NOT SCALE DRAWING	DB25F TO 8-XLRM, RoHS			DB25FXLRM			C				
Λ															

SolidWorks CAD File B

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Switchcraft: DB25M10XLRM