



SCHEMATIC CIRCUIT 1A WITH LEDs



NOTES:

 \rightarrow

- 1. SPECIFICATIONS:
 ALTERNATE ACTION
 SWITCH:SINGLE POLE N.O. FOR CONTROLLING LOADS
 KEY TRAVEL 0.14 INCHES
 GOLD CONTACT FINISH IN CONTACT AREA
 SWITCHING VOLTAGE OF N.O. CONTACTS: 28VOLTS DC
 MAXIMUM SWITCHING CURRENT 250mA
 LED VOLTAGE 4.75 TO 28 VOLTS DC AT RED WIRE REF
 TO BLACK WIRE
 OPERATING LIFE 100,000 CYCLES
 OPERATING TEMPERATURE -25 TO +75°C
 ACTUATING FORCE LESS THAN 3 lb
 IP66
- 2. MATERIALS:
 SWITCH HOUSING: GRAY THERMOPLASTIC
 ACTUATING BUTTON: NATURAL COLORED ELASTOMER
 CONTACTS: COPPER ALLOY WITH
 GOLD PLATING IN CONTACT AREA
 TERMINALS COPPER ALLOY, PLATED TIN
 STRAIN RELIEF: NATURAL COLORED ELASTOMER
 CABLE: 4 CONDUCTOR, 26 AWG STRANDED, GRAY PVC JACKET



CUSTOMER DRAWING

38.4]

Ø1.08 REF [27.4]

			3 3			THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.								
					UNLESS OTHERWISE SPECIFIED	SIZE *	W	IDTH *	MULT	*	LBS/M *	TE	MPER *	
					1. ALL DIMENSIONS IN INCHES [mm]	FINISH *			•	MATERIAL		*		
					- TWO PLACE DECIMALS ±0.02 [0.5]	SPEC No.		*		SPEC No	∑ No. *			
					-THREE PLACE DECIMALS ±0.005 [0.13]	FIRST U	SED ON		SCALE 1:1	@n	7 <u> </u>		اهر	GC,
						DATE DRAWN	BY	CHKD						JU
_		0.4.4=	000	- 114		1-14-16	SRC	12-5-16	TJK					
А	ECO 27837	2-1-17	SRC	TJK		1 14 10	0110	SRC	2-1-17		SHEET 1	OF	1	
REV	ECO NUMBER	DATE	BY	APVD		NAME				PART No				REV
REVISIONS					DO NOT SCALE DRAWING	PENDANT, PL-PR WITH BLUE LED			LUE LED	E921KALN				Α

4

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Switchcraft: E921KALN