

## SC700CT A/V Direct Box Audio Specifications

## Switchcraft®

Parameter	Performance	Conditions	
Frequency Response	20Hz - 20kHz	+/-0.3dB, ref 1kHz	
Total Harmonic Distortion + Noise	< 0.009% < 0.5%	at 1kHz, +4dBu Input, 22kHz Bandwidth at 20Hz, +4dBu Input, 22kHz Bandwidth	
Maximum Input Level	+18dBu	at 20Hz with 1% THD+Noise at 1kHz at 1kHz	
Input Impedance	> 120kΩ		
Output Impedance	< 50Ω		
Common Mode Rejection Ratio (CMRR)	> 85dB	at 60Hz	
Deviation from Linear Phase	< 7° < 1° < 13°	at 20Hz at 1kHz at 20kHz	
Voltage Gain	-23dB -43dB	+/-1dB +/-1dB with 20dB pad engaged	
Pad Attenuation	20dB	+/-1dB	

Notes: All measurements were taken with a  $25\Omega$  unbalanced source and measured from the XLR with a  $1k\Omega$  balanced load. Specifications subject to change without notice.

**CUSTOMER DRAWING** 


SCALE 1:1	Sara Dana	(GD®
DATE DRAWN		
3/2/10	SHEET 2 OF 3	
DRAWN BY	PART No.	REV
BHM	SC700CT	U

7

4

3

SolidWorks CAD File C



## **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Switchcraft:

SC700CT