



NOTES:

1. MEETS SMPTE 2082-1
CHARACTERISTIC IMPEDANCE: 75 OHMS
CONTACT RESISTANCE: LESS THAN 50 MILLIOHMS
2. MATERIAL:
PLUG BARREL: COPPER ALLOY, SILVER PLATED.
PLUG HANDLE: COPPER ALLOY, NICKEL PLATED
CONTACT: COPPER ALLOY, SILVER PLATED
INSULATORS: TEFLON
3. THIS PRODUCT IS RoHS COMPLIANT.

CUSTOMER DRAWING

						THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.									
					UNLESS OTHERWISE SPECIFIED 1. ALL DIMENSIONS IN INCHES [mm] - TWO PLACE DECIMALS ±0.02 [0.5] - THREE PLACE DECIMALS ±0.005 [0.13]	SIZE		WIDTH		MULT		LBS/M		TEMPER	
						FINISH SPEC No.						MATERIAL SPEC No.			
						FIRST USED ON				SCALE 2:1		Switchcraft®			
						DATE DRAWN 5/01/17		BY PNK	CHKD PNK 5/01/17		APVD SRC 5/01/17				
A	28195	08/29/19	PC	TJK		SHEET 1 OF 1									
REV	ECO NUMBER	DATE	BY	APVD											
REVISIONS					DO NOT SCALE DRAWING	NAME TERMINATING PLUG UHD SINGLE MICRO. RoHS						PART No. VMMSTPUHD		REV A	

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Switchcraft:](#)

[VMMSTPUHD](#)