



- NOTES:
1. MEETS SMPTE 2082-1
CHARACTERISTIC IMPEDANCE :75 OHMS
CONTACT RESISTANCE: 50 MILLIOHMS MAX.
 2. MATERIAL:
PLUG: COPPER ALLOY, SILVER PLATED.
CONTACT: COPPER ALLOY, SILVER PLATED.
INSULATOR: TEFLON
OVERMOLD: THERMOPLASTIC ELASTOMER
 3. THIS PRODUCT IS RoHS COMPLIANT.

CUSTOMER DRAWING

					<div>UNLESS OTHERWISE SPECIFIED</div> <div>1. ALL DIMENSIONS IN INCHES [mm]</div> <div>- TWO PLACE DECIMALS ±0.02 [0.5]</div> <div>- THREE PLACE DECIMALS ±0.005 [0.13]</div>	THIS DRAWING DESCRIBES A DESIGN CONSIDERED PROPRIETARY IN NATURE, DEVELOPED AND MANUFACTURED BY SWITCHCRAFT INC. AND IS RELEASED ON A CONFIDENTIAL BASIS FOR IDENTIFICATION PURPOSES ONLY.														
						SIZE	WIDTH		MULT		LBS/M		TEMPER							
						FINISH						MATERIAL								
						SPEC No.						SPEC No.								
						FIRST USED ON				SCALE		Switchcraft®								
										3:2										
A	28195	08/29/19	PC	TJK		DATE DRAWN	BY	CHKD		APVD		SHEET 1 OF 1								
						5/01/17	PNK	PNK		SRC										
							5/01/17		5/01/17											
REV	ECO NUMBER	DATE	BY	APVD	NAME					PART No.					REV					
REVISIONS					DO NOT SCALE DRAWING					DUAL TERMINATED PLUG UHD MICRO, OVERMOLDED, RoHS					VMMTPUHD					A

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Switchcraft:](#)

[VMMTPUHD](#)