

1A, 50V - 600V Glass Passivated Super Fast Rectifiers

FEATURES

- High efficiency, low VF
- High current capability
- High reliability
- High surge current capability
- Low power loss
- Compliant to RoHS Directive 2011/65/EU and in accordance to WEEE 2002/96/EC
- Halogen-free according to IEC 61249-2-21



TS-1



MECHANICAL DATA

Case: TS-1

Molding compound, UL flammability classification rating 94V-0

Part no. with suffix "H" means AEC-Q101 qualified

Packing code with suffix "G" means green compound (halogen-free)

Terminal: Pure tin plated leads, solderable per JESD22-B102

Meet JESD 201 class 2 whisker test

Weight: 0.2g (approximately)

MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS (T _A =25°C unless otherwise noted)										
PARAMETER	SYMBOL	SFT 11G	SFT 12G	SFT 13G	SFT 14G	SFT 15G	SFT 16G	SFT 17G	SFT 18G	UNIT
Maximum repetitive peak reverse voltage	V _{RRM}	50	100	150	200	300	400	500	600	V
Maximum RMS voltage	V _{RMS}	35	70	105	140	210	280	350	420	V
Maximum DC blocking voltage	V _{DC}	50	100	150	200	300	400	500	600	V
Maximum average forward rectified current	I _{F(AV)}	1								A
Peak forward surge current, 8.3 ms single half sine-wave superimposed on rated load	I _{FSM}	30								A
Maximum instantaneous forward voltage (Note 1) @ 1 A	V _F	0.95			1.3		1.7			V
Maximum reverse current @ rated V _R T _J =25°C T _J =125°C	I _R	5 100								μA
Maximum reverse recovery time (Note 2)	t _{rr}	35								ns
Typical junction capacitance (Note 3)	C _J	20			10					pF
Typical thermal resistance	R _{θJA}	100								°C/W
Operating junction temperature range	T _J	- 55 to +150								°C
Storage temperature range	T _{STG}	- 55 to +150								°C

Note 1: Pulse test with PW=300μs, 1% duty cycle

Note 2: Reverse Recovery Test Conditions: I_F=0.5A, I_R=1.0A, I_{RR}=0.25A

Note 3: Measured at 1 MHz and Applied Reverse Voltage of 4.0V D.C.

ORDERING INFORMATION					
PART NO.	PART NO. SUFFIX	PACKING CODE	PACKING CODE SUFFIX (*)	PACKAGE	PACKING
SFT1xG (Note 1)	H	A0	G	TS-1	3,000 / Ammo box (52mm taping)
		A1		TS-1	3,000 / Ammo box (26mm taping)
		R0		TS-1	5,000 / 13" Paper reel
		B0		TS-1	1,000 / Bulk packing

Note 1: "x" defines voltage from 50V (SFT11G) to 600V (SFT18G)

*: Optional available

EXAMPLE					
PREFERRED P/N	PART NO.	PART NO. SUFFIX	PACKING CODE	PACKING CODE SUFFIX	DESCRIPTION
SFT16GHA0G	SFT16G	H	A0	G	AEC-Q101 qualified Green compound

RATINGS AND CHARACTERISTICS CURVES

(T_A=25°C unless otherwise noted)

FIG.1 MAXIMUM AVERAGE FORWARD CURRENT DERATING




FIG.2 TYPICAL REVERSE CHARACTERISTICS



FIG. 3 MAXIMUM NON-REPETITIVE FORWARD SURGE CURRENT



FIG. 4 TYPICAL FORWARD CHARACTERISTICS




FIG. 5 TYPICAL JUNCTION CAPACITANCE





FIG.6 REVERSE RECOVERY TIME CHARACTERISTIC AND TEST CIRCUIT DIAGRAM



PACKAGE OUTLINE DIMENSIONS

TS-1



DIM.	Unit (mm)		Unit (inch)	
	Min	Max	Min	Max
A	2.00	2.70	0.079	0.106
B	0.53	0.64	0.021	0.025
C	25.40	-	1.000	-
D	3.00	3.30	0.118	0.130
E	25.40	-	1.000	-

MARKING DIAGRAM



P/N = Specific Device Code
G = Green Compound
YW = Date Code
F = Factory Code

Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.

Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Taiwan Semiconductor:

[SFT11G](#) [SFT13G](#) [SFT14G](#) [SFT15G](#) [SFT16G](#) [SFT17G](#) [SFT18G](#) [SFT12G R0](#) [SFT12GHR0G](#) [SFT18G R0G](#)
[SFT13GHR0G](#) [SFT17G R0](#) [SFT12G R0G](#) [SFT15G R0G](#) [SFT16GHR0G](#) [SFT18GHR0G](#) [SFT15GHR0G](#) [SFT15G R0](#)
[SFT11G R0](#) [SFT14G R0G](#) [SFT11G R0G](#) [SFT11GHR0G](#) [SFT13G R0](#) [SFT18G R0](#) [SFT13G R0G](#) [SFT16G R0G](#)
[SFT14GHR0G](#) [SFT17GHR0G](#) [SFT17G R0G](#) [SFT16G R0](#) [SFT14G R0](#) [SFT11GHA0G](#) [SFT14GHA0G](#)
[SFT14GHA1G](#) [SFT14GHB0G](#) [SFT15G A0G](#) [SFT15G A1G](#) [SFT18GHB0G](#) [SFT11G A0G](#) [SFT11G A1G](#) [SFT11G](#)
[B0G](#) [SFT14G A1G](#) [SFT14G B0G](#) [SFT17GHB0G](#) [SFT18G A0G](#) [SFT18G A1G](#) [SFT18G B0G](#) [SFT18GHA0G](#)
[SFT18GHA1G](#) [SFT16GHB0G](#) [SFT17G A0G](#) [SFT17G A1G](#) [SFT17G B0G](#) [SFT17GHA0G](#) [SFT17GHA1G](#)
[SFT15GHB0G](#) [SFT16G A0G](#) [SFT16G A1G](#) [SFT16G B0G](#) [SFT16GHA0G](#) [SFT16GHA1G](#) [SFT13GHA1G](#)
[SFT13GHB0G](#) [SFT14G A0G](#) [SFT15G B0G](#) [SFT15GHA0G](#) [SFT15GHA1G](#) [SFT12GHA1G](#) [SFT12GHB0G](#) [SFT13G](#)
[A0G](#) [SFT13G A1G](#) [SFT13G B0G](#) [SFT13GHA0G](#) [SFT11GHA1G](#) [SFT11GHB0G](#) [SFT12G A0G](#) [SFT12G A1G](#)
[SFT12G B0G](#) [SFT12GHA0G](#) [SFT14GH](#) [SFT15GH](#) [SFT16GH](#) [SFT18GH](#)