


## Schottky Barrier Rectifier

### FEATURES

- Low forward voltage drop
- Low power loss, high efficiency
- Guardring for overvoltage protection
- High surge current capability
- For use as Bypass diode in Solar application.
- Compliant to RoHS Directive 2011/65/EU and in accordance to WEEE 2002/96/EC
- Halogen-free according to IEC 61249-2-21 definition



R-6

### MECHANICAL DATA

**Case:** R-6

Molding compound, UL flammability classification rating 94V-0

Base P/N with suffix "G" on packing code - halogen-free

Base P/N with prefix "H" on packing code - AEC-Q101 qualified

**Terminal:** Matte tin plated leads, solderable per JESD22-B102

Meet JESD 201 class 1A whisker test,

with prefix "H" on packing code meet JESD 201 class 2 whisker test

**Weight:** 1.7 g (approximately)

| MAXIMUM RATINGS AND ELECTRICAL CHARACTERISTICS (T <sub>A</sub> =25℃ unless otherwise noted)             |                    |                      |        |        |                  |
|---------------------------------------------------------------------------------------------------------|--------------------|----------------------|--------|--------|------------------|
| PARAMETER                                                                                               | SYMBOL             | SR1502               | SR1503 | SR1504 | UNIT             |
| Maximum repetitive peak reverse voltage                                                                 | V <sub>RRM</sub>   | 20                   | 30     | 40     | V                |
| Maximum RMS voltage                                                                                     | V <sub>RMS</sub>   | 14                   | 21     | 28     | V                |
| Maximum DC blocking voltage                                                                             | V <sub>DC</sub>    | 20                   | 30     | 40     | V                |
| Maximum average forward rectified current                                                               | I <sub>F(AV)</sub> | 15                   |        |        | A                |
| Repetitive peak forward current f > 15Hz                                                                | I <sub>FRM</sub>   | 60                   |        |        | A                |
| Peak forward surge current, 50/60 Hz single half sine-wave superimposed on rated load (JEDEC Method )   | I <sub>FSM</sub>   | 300 / 340            |        |        | A                |
| Rating for fusing t < 10ms                                                                              | I <sup>2</sup> t   | 390                  |        |        | A <sup>2</sup> s |
| Maximum instantaneous forward voltage @5 A<br>(Note 1) @15 A                                            | V <sub>F</sub>     | 0.45<br>0.55         |        |        | V                |
| Maximum DC reverse current @T <sub>J</sub> =25 ℃<br>at rated DC blocking voltage @T <sub>J</sub> =100 ℃ | I <sub>R</sub>     | 500<br>20            |        |        | μA<br>mA         |
| Typical thermal resistance                                                                              | R <sub>θJL</sub>   | 2.5                  |        |        | °C/W             |
|                                                                                                         | R <sub>θJA</sub>   | 25                   |        |        |                  |
| Junction temperature range<br>- in DC forward mode                                                      | T <sub>J</sub>     | - 50 to +150<br>≤200 |        |        | °C               |
| Storage temperature range                                                                               | T <sub>STG</sub>   | - 55 to +175         |        |        | °C               |

Note 1: Pulse test with PW=300μs, 1% duty cycle

| ORDERING INFORMATION |                    |              |                     |         |                        |
|----------------------|--------------------|--------------|---------------------|---------|------------------------|
| PART NO.             | AEC-Q101 QUALIFIED | PACKING CODE | GREEN COMPOUND CODE | PACKAGE | PACKING                |
| SR15xx<br>(Note 1)   | Prefix "H"         | A0           | Suffix "G"          | R-6     | 700 / Ammo box         |
|                      |                    | R0           |                     | R-6     | 1,000 / 13" Paper reel |
|                      |                    | B0           |                     | R-6     | 400 / Bulk packing     |

Note 1: "xx" defines voltage from 20V (SR1502) to 40V (SR1504)

| EXAMPLE       |          |                    |              |                     |                    |
|---------------|----------|--------------------|--------------|---------------------|--------------------|
| PREFERRED P/N | PART NO. | AEC-Q101 QUALIFIED | PACKING CODE | GREEN COMPOUND CODE | DESCRIPTION        |
| SR1504 A0     | SR1504   |                    | A0           |                     |                    |
| SR1504 A0G    | SR1504   |                    | A0           | G                   | Green compound     |
| SR1504HA0     | SR1504   | H                  | A0           |                     | AEC-Q101 qualified |

## RATINGS AND CHARACTERISTICS CURVES

(TA=25°C unless otherwise noted)

FIG.1 RATED FORWARD CURRENT VS AMBIENT TEMP. CURVE




FIG. 2 MAXIMUM FORWARD SURGE CURRENT




FIG. 3 TYPICAL FORWARD CHARACTERISTICS




FIG. 4 TYPICAL REVERSE CHARACTERISTICS




FIG. 5 TYPICAL JUNCTION CAPACITANCE






FIG. 6 TYPICAL TRANSIENT THERMAL RESISTANCE



PACKAGE OUTLINE DIMENSIONS



| DIM. | Unit (mm) |      | Unit (inch) |       |
|------|-----------|------|-------------|-------|
|      | Min       | Max  | Min         | Max   |
| A    | 6.80      | 7.20 | 0.268       | 0.283 |
| B    | 1.20      | 1.30 | 0.047       | 0.051 |
| C    | 25.40     | -    | 1.000       | -     |
| D    | 8.60      | 9.10 | 0.339       | 0.358 |
| E    | 25.40     | -    | 1.000       | -     |

MARKING DIAGRAM



P/N = Specific Device Code  
 G = Green Compound  
 YWW = Date Code  
 F = Factory Code

### **Notice**

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.

# Mouser Electronics

Authorized Distributor

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

[Taiwan Semiconductor:](#)

[SR1502](#) [SR1503](#) [SR1504](#) [SR1504 R0](#) [SR1502 R0](#) [SR1504HR0G](#) [SR1503HR0G](#) [SR1502HR0](#) [SR1504 R0G](#)  
[SR1503HR0](#) [SR1503 R0G](#) [SR1502HR0G](#) [SR1502 R0G](#) [SR1504HR0](#) [SR1503 R0](#)